

PHPDOCX



Contents

Package create Procedural Elements	2
CreateDocx.inc	2
Package create Classes	3
Class CreateDocx	3
Class Constant NAMESPACEWORD	3
Class Constant SCHEMA_IMAGEDOCUMENT	3
Class Constant SCHEMA_OFFICEDOCUMENT	3
Var \$fileGraphicTemplate	3
Var \$graphicTemplate	4
Var \$intIdWord	4
Var \$log	4
Constructor construct	4
Method addBreak	5
Method addFont	5
Method addFooter	5
Method addGraphic	6
Method addHeader	6
Method addImage	6
Method addLink	7
Method addList	7
Method addMathDocx	8
Method addMathEq	8
Method addParagraph	8
Method addTable	9
Method addTableContents	9
Method addText	9
Method addTitle	10
Method createDocx	10
Method fAddBreak	11
Method fAddFont	11
Method fAddFooter	11
Method fAddGraphic	12
Method fAddHeader	12
Method fAddImage	12
Method fAddLink	13
Method fAddList	13
Method fAddMathDocx	14
Method fAddMathEq	14
Method fAddParagraph	14
Method fAddTable	15
Method fAddTableContents	15
Method fAddText	15
Method fAddTitle	16

Method fCreateDocx	16
Method fSetDefaultFont	17
Method getXmlContentTypes	17
Method getXmlDocPropsApp	17
Method getXmlDocPropsCore	17
Method getXmlRels Rels	18
Method getXmlWordDocumentContent	18
Method getXmlWordEndnotes	18
Method getXmlWordFontTable	18
Method getXmlWordFooter1	18
Method getXmlWordHeader1	19
Method getXmlWordRelsDocumentRels	19
Method getXmlWordSettings	19
Method getXmlWordStyles	19
Method getXmlWordThemeTheme1	20
Method getXmlWordWebSettings	20
Method setDefaultFont	20
Method setEncodeUTF8	20
Method setLanguage	21
Method setXmlContentTypes	21
Method setXmlDocPropsApp	21
Method setXmlDocPropsCore	22
Method setXmlRelsRels	22
Method setXmlWordDocument	22
Method setXmlWordEndnotes	23
Method setXmlWordFontTable	23
Method setXmlWordFooter1	23
Method setXmlWordHeader1	24
Method setXmlWordRelsDocumentRels	24
Method setXmlWordSettings	24
Method setXmlWordStyles	25
Method setXmlWordThemeTheme1	25
Method setXmlWordWebSettings	25
Method _destruct	26
Method _toString	26

Package elements Procedural Elements	28
CreateChartRels.inc	28
CreateElement.inc	29
CreateExcelSharedStrings.inc	30
CreateExcelSheet.inc	31
CreateExcelTable.inc	32
CreateFontTable.inc	33
CreateFooter.inc	34
CreateFootnote.inc	35
CreateGraphic.inc	36
CreateHeader.inc	37
CreateImage.inc	38
CreateLink.inc	39
CreateList.inc	40

CreatePage.inc	41
CreateSettings.inc	42
CreateStyle.inc	43
CreateStyleTable.inc	44
CreateTable.inc	45
CreateTableContents.inc	46
CreateText.inc	47
CreateTheme1.inc	48
CreateWebSettings.inc	49
CreateXlsx.inc	50
TransformDoc.inc	51
Package elements Classes	52
Class CreateChartRels	52
Var \$ xml	52
Constructor __construct	52
Method createRelationship	53
Method generateRELATIONSHIP	53
Method generateRELATIONSHIPS	53
Method getInstance	54
Method __destruct	54
Method __toString	54
Class CreateElement	54
Class Constant MATHNAMESPACEWORD	55
Class Constant NAMESPACEWORD	55
Var \$ xml	55
Constructor __construct	55
Method cleanTemplate	55
Method cleanTemplateFirstRPR	55
Method generateANCHOR	56
Method generateAVLST	56
Method generateB	56
Method generateBCS	57
Method generateBLIP	57
Method generateBLIPFILL	57
Method generateCNVGRAPHICFRAMEPR	57
Method generateCNVPICPR	58
Method generateCNVPR	58
Method generateDOCPR	58
Method generateDRAWING	59
Method generateEFFECTEXTENT	59
Method generateEXT	59
Method generateEXTENT	60
Method generateFILLRECT	60
Method generateGRAPHIC	60
Method generateGRAPHICDATA	61
Method generateGRAPHICPRAMELOCKS	61
Method generateINLINE	61
Method generateJC	62
Method generateLINETO	62

Method generateLN	62
Method generateNOPROOF	63
Method generateNVPICPR	63
Method generateOFF	63
Method generateP	63
Method generatePIC	64
Method generatePOSITIONH	64
Method generatePOSITIONV	64
Method generatePOSOFFSET	65
Method generatePPR	65
Method generatePRSTDASH	65
Method generatePRSTGEOM	66
Method generatePSTYLE	66
Method generateQUITAR	66
Method generateR	67
Method generateRFonts	67
Method generateRPR	67
Method generateRSTYLE	67
Method generateSCHEMECLR	68
Method generateSIMPLEPOS	68
Method generateSOLIDFILL	68
Method generateSPPR	69
Method generateSTART	69
Method generateSTRETCH	69
Method generateT	69
Method generateWRAPNONE	70
Method generateWRAPPOLYGON	70
Method generateWRAPSQUARE	70
Method generateWRAPTHROUGH	71
Method generateWRAPTOPANDBOTTOM	71
Method generateXFRM	71
Method __destruct	71
Method __toString	72
Class CreateExcelSharedStrings	72
Constructor __construct	72
Method createExcelSharedStrings	72
Method generateSI	73
Method generateSST	73
Method generateT	73
Method getInstance	74
Method __destruct	74
Method __toString	74
Class CreateExcelSheet	74
Constructor __construct	75
Method createExcelSheet	75
Method generateC	75
Method generateCOL	76
Method generateCOLS	76
Method generateDIMENSION	76

Method generatePAGEMARGINS	77
Method generatePAGESETUP	77
Method generateROW	77
Method generateSELECTION	78
Method generateSHEETDATA	78
Method generateSHEETFORMATPR	78
Method generateSHEETVIEW	79
Method generateSHEETVIEWS	79
Method generateTABLEPART	79
Method generateTABLEPARTS	80
Method generateV	80
Method generateWORKSHEET	80
Method getInstance	81
Method destruct	81
Method toString	81
Class CreateExcelTable	81
Constructor construct	82
Method createExcelTable	82
Method generateTABLE	82
Method generateTABLECOLUMN	82
Method generateTABLECOLUMNS	83
Method generateTABLESTYLEINFO	83
Method getInstance	84
Method destruct	84
Method toString	84
Class CreateFontTable	84
Var \$ xml	85
Constructor construct	85
Method createFont	85
Method generateCHARSET	85
Method generateFAMILY	86
Method generateFONT	86
Method generatePANOSE1	86
Method generatePITCH	87
Method generateSIG	87
Method getInstance	88
Method destruct	88
Method toString	88
Class CreateFooter	88
Constructor construct	89
Method createFooter	89
Method generateFLDSIMPLE	89
Method generateFTR	89
Method generateP	90
Method generatePTAB	90
Method generateR	90
Method getInstance	90
Method destruct	91
Method toString	91

Class CreateFootnote	91
Var \$init	91
Constructor __construct	92
Method createDocumentFootnote	92
Method createFootnote	92
Method createInitFootnote	92
Method generateFOOTNOTE	93
Method generateFOOTNOTEREF	93
Method generateFOOTNOTEREFERENCE	93
Method generateP	94
Method generatePPR	94
Method generateR	94
Method generateSEPARATOR	95
Method generateSPACING	95
Method getInstance	95
Method __destruct	95
Method __toString	96
Class CreateGraphic	96
Class Constant NAMESPACEWORD	96
Var \$ xmlChart	96
Constructor __construct	96
Method createCHARTXML	97
Method createDOCUEMNTXML	97
Method createGraphic	97
Method generateAUTO	98
Method generateAUTOTITLEDELETED	98
Method generateAXAXID	98
Method generateAXID	99
Method generateAXPOS	99
Method generateBARCHART	99
Method generateBARDIR	100
Method generateBODYPR	100
Method generateCAT	100
Method generateCATAX	100
Method generateCHART	101
Method generateCHARTSPACE	101
Method generateCROSSAX	101
Method generateCROSSBETWEEN	101
Method generateCROSSES	102
Method generateDATE1904	102
Method generateDEFRPR	102
Method generateDLBLS	103
Method generateDOCUMENTCHART	103
Method generateEXTERNALDATA	103
Method generateF	103
Method generateFIRSTSLICEANG	104
Method generateFORMATCODE	104
Method generateGROUPING	104
Method generateIDX	105

Method generateLANG	105
Method generateLAYOUT	105
Method generateLBLALGN	106
Method generateLBLOFFSET	106
Method generateLEGEND	106
Method generateLEGENDFONT	107
Method generateLEGENDPOS	107
Method generateLINECHART	107
Method generateLN	108
Method generateLSTSTYLE	108
Method generateMAJORGRIDLINES	108
Method generateNOFILL	108
Method generateNUMCACHE	108
Method generateNUMFMT	109
Method generateNUMREF	109
Method generateORDER	109
Method generateORIENTATION	109
Method generateOVERLAP	110
Method generatePIECHART	110
Method generatePLOTAREA	110
Method generatePLOTVISONLY	111
Method generatePT	111
Method generatePTCOUNT	111
Method generateRICH	112
Method generateSCALING	112
Method generateSER	112
Method generateSHAPE	112
Method generateSHOWPERCENT	113
Method generateSPPR	113
Method generateSTRCACHE	113
Method generateSTRREF	113
Method generateSTYLE	114
Method generateTICKLBLPOS	114
Method generateTITLE	114
Method generateTITLELAYOUT	115
Method generateTITLEP	115
Method generateTITLEPPR	115
Method generateTITLER	115
Method generateTITLERFONTS	115
Method generateTITLERPR	116
Method generateTITLET	116
Method generateTITLETX	117
Method generateTX	117
Method generateV	117
Method generateVAL	117
Method generateVALAX	118
Method generateVARYCOLORS	118
Method getInstance	118
Method getName	118

Method <u>getRId</u>	118
Method <u>getXmlChart</u>	119
Method <u>setName</u>	119
Method <u>setRId</u>	119
Method <u>setXmlChart</u>	120
Method <u>destruct</u>	120
Method <u>toString</u>	120
Class <u>CreateHeader</u>	120
Constructor <u>construct</u>	121
Method <u>createHeader</u>	121
Method <u>generateHDR</u>	121
Method <u>generateP</u>	122
Method <u>getInstance</u>	122
Method <u>destruct</u>	122
Method <u>toString</u>	122
Class <u>CreateImage</u>	122
Class Constant <u>CONSTWORD</u>	123
Class Constant <u>NAMESPACEWORD</u>	123
Class Constant <u>NAMESPACEWORD1</u>	123
Class Constant <u>NAMESPACEWORD2</u>	123
Class Constant <u>TAMBORDER</u>	123
Constructor <u>construct</u>	123
Method <u>createImage</u>	123
Method <u>getInstance</u>	124
Method <u>getName</u>	124
Method <u>getRId</u>	124
Method <u>setName</u>	124
Method <u>setRId</u>	125
Method <u>destruct</u>	125
Method <u>toString</u>	125
Class <u>CreateLink</u>	125
Constructor <u>construct</u>	126
Method <u>createLink</u>	126
Method <u>generateFLDCHAR</u>	126
Method <u>generateHYPERLINK</u>	127
Method <u>generateINSTRTEXT</u>	127
Method <u>generatePROOFERR</u>	127
Method <u>generateR</u>	128
Method <u>generateRSTYLE</u>	128
Method <u>getFont</u>	128
Method <u>getInstance</u>	128
Method <u>getLink</u>	129
Method <u>getTitle</u>	129
Method <u>destruct</u>	129
Method <u>toString</u>	129
Class <u>CreateList</u>	130
Var <u>\$data</u>	130
Var <u>\$font</u>	130
Var <u>\$list</u>	130

Var \$val	131
Constructor <u>construct</u>	131
Method <u>addList</u>	131
Method <u>createList</u>	131
Method <u>generateILFO</u>	132
Method <u>generateLVL</u>	132
Method <u>generateLISTPR</u>	132
Method <u>generateNUMID</u>	133
Method <u>generateNUMPR</u>	133
Method <u>generatePSTYLE</u>	133
Method <u>getInstance</u>	134
Method <u>runArray</u>	134
Method <u>destruct</u>	134
Method <u>toString</u>	134
Class <u>CreatePage</u>	135
Var \$ <u>xml</u>	135
Constructor <u>construct</u>	135
Method <u>createPage</u>	135
Method <u>createSECTPR</u>	136
Method <u>generateBR</u>	136
Method <u>generateCOL</u>	136
Method <u>generateCOLS</u>	137
Method <u>generateDOCGRID</u>	137
Method <u>generatePageBreak</u>	137
Method <u>generatePGMAR</u>	138
Method <u>generatePGSZ</u>	138
Method <u>generateSECTIONSECTPR</u>	138
Method <u>generateSECTPR</u>	139
Method <u>generateTITLEPG</u>	139
Method <u>getInstance</u>	139
Method <u>destruct</u>	140
Method <u>toString</u>	140
Class <u>CreateSettings</u>	140
Var \$ <u>xml</u>	140
Constructor <u>construct</u>	141
Method <u>generateSettings</u>	141
Method <u>getInstance</u>	141
Method <u>destruct</u>	141
Method <u>toString</u>	141
Class <u>CreateStyle</u>	142
Var \$ <u>xml</u>	142
Constructor <u>construct</u>	142
Method <u>addStyle</u>	142
Method <u>addStyleTable</u>	143
Method <u>createStyle</u>	143
Method <u>generateAUTOREDEFINE</u>	144
Method <u>generateB</u>	144
Method <u>generateBASEDON</u>	144
Method <u>generateBCS</u>	144

Method generateBOTTOM	144
Method generateCOLOR	145
Method generateCONTEXTUALSPACING	145
Method generateI	145
Method generateICS	146
Method generateLVL	146
Method generateIND	146
Method generateKEEPLINES	147
Method generateKEEPNEXT	147
Method generateKERN	147
Method generateLEFT	148
Method generateLINK	148
Method generateNAME	148
Method generateNEXT	149
Method generateNUMPR	149
Method generateOUTLINELVL	149
Method generatePBDR	150
Method generatePBDR_BOTTOM	150
Method generatePPR	150
Method generateQFORMAT	150
Method generateRFonts	151
Method generateRFonts2	151
Method generateRIGHT	151
Method generateRPR	152
Method generateRPR_SPACING	152
Method generateRSID	152
Method generateSEMIHIDDEN	153
Method generateSHD	153
Method generateSPACING	153
Method generateSTYLE	154
Method generateSZ	154
Method generateSZCS	154
Method generateTABCENTER	155
Method generateTABRIGHT	155
Method generateTABS	155
Method generateTBLBORDERS	156
Method generateTBLBORDERS_BOTTOM	156
Method generateTBLBORDERS_INSIDEH	156
Method generateTBLBORDERS_INSIDEV	157
Method generateTBLBORDERS_LEFT	157
Method generateTBLBORDERS_RIGHT	158
Method generateTBLBORDERS_TOP	158
Method generateTBLCELLMAR	159
Method generateTBLIND	159
Method generateTBLPR	159
Method generateTBLSTYLECOLBANDSIZE	159
Method generateTBLSTYLEROWBANDSIZE	160
Method generateTCPR	160
Method generateTOP	160

Method generateU	161
Method generateUIPRIORITY	161
Method generateUNHIDEWHENUSED	161
Method generateVERTALIGN	162
Method getInstance	162
Method destruct	162
Method toString	162
Class CreateTable	163
Var \$ xml	163
Constructor construct	163
Method addStyleTable	163
Method generateSHD	164
Method generateTBLPR	164
Method generateTBLSTYLEPR	164
Method generateTCBORDERS	165
Method generateTCPR	165
Method getInstance	165
Method destruct	165
Method toString	165
Class CreateTable	166
Constructor construct	166
Method addList	166
Method createTable	167
Method generateGRIDCOLS	167
Method generateHMERGE	167
Method generateJC	168
Method generateP	168
Method generateSHD	168
Method generateTBL	169
Method generateTBLBORDERS	169
Method generateTBLBOTTOM	169
Method generateTBLCELLSPACING	170
Method generateTBLGRID	170
Method generateTBLINSIDEH	170
Method generateTBLINSIDEV	171
Method generateTBLLEFT	171
Method generateTBLLOOK	171
Method generateTBLOVERLAP	172
Method generateTBLPR	172
Method generateTBLRIGHT	172
Method generateTBLSTYLE	173
Method generateTBLTOP	173
Method generateTBLW	173
Method generateTC	174
Method generateTCPR	174
Method generateTCW	174
Method generateTR	175
Method generateTRPR	175
Method generateVMERGE	175

Method getInstance	175
Method destruct	175
Method toString	176
Class CreateTableContents	176
Var \$ xml	176
Constructor construct	177
Method createTableContents	177
Method generateFLDSIMPLE	177
Method getInstance	177
Method destruct	178
Method toString	178
Class CreateText	178
Class Constant IDTITLE	179
Constructor construct	179
Method createText	179
Method createTitle	179
Method generateB	179
Method generateBOOKMARKEND	180
Method generateBOOKMARKSTART	180
Method generateCOLOR	181
Method generateI	181
Method generateJC	181
Method generatePAGEBREAKBEFORE	182
Method generatePSTYLE	182
Method generateSZ	182
Method generateU	183
Method generateWIDOWCONTROL	183
Method generateWORDWRAP	183
Method getInstance	184
Method destruct	184
Method toString	184
Class CreateTheme1	184
Class Constant NAMESPACEWORD	185
Var \$ xml	185
Constructor construct	185
Method createTheme	185
Method generateACCENT1	186
Method generateACCENT2	186
Method generateACCENT3	186
Method generateACCENT4	186
Method generateACCENT5	186
Method generateACCENT6	187
Method generateALPHA	187
Method generateBEVELT	187
Method generateBGFILLSTYLELST	188
Method generateCAMERA	188
Method generateCLRScheme	188
Method generateCS	188
Method generateDK1	189

Method generateDK2	189
Method generateEA	189
Method generateEFFECTLST	190
Method generateEFFECTLST2	190
Method generateEFFECTSTYLE	190
Method generateEFFECTSTYLE2	190
Method generateEFFECTSTYLELST	190
Method generateEXTRACLRSCHEMELST	191
Method generateFILLSTYLELST	191
Method generateFILLTORECT	191
Method generateFMTSCHEME	191
Method generateFOLHLINK	192
Method generateFONT	192
Method generateFONT2	192
Method generateFONT3	193
Method generateFONTSCHEMA	193
Method generateGRADFILL	193
Method generateGRADFILL2	194
Method generateGS	194
Method generateGS2	194
Method generateGSLST	195
Method generateHLINK	195
Method generateLATIN	195
Method generateLIGHTRIG	196
Method generateLIN	196
Method generateLN	196
Method generateLN2	197
Method generateLNSTYLELST	197
Method generateLT1	197
Method generateLT2	197
Method generateMAYORFONT	198
Method generateMINORFONT	198
Method generateOBJECTDEFAULTS	198
Method generateOUTERSHDW	198
Method generatePATH	199
Method generatePRSTDASH	199
Method generateROT	199
Method generateSATMOD	200
Method generateSCENE3D	200
Method generateSCHEMECLR	200
Method generateSCHEMECLR2	201
Method generateSCHEMECLR3	201
Method generateSHADE	201
Method generateSOLIDFILL	202
Method generateSP3D	202
Method generateSRGBCLR	202
Method generateSRGBCLR2	202
Method generateSYSCLR	203
Method generateTHEMEELEMENTS	203

Method generateTINT	203
Method generateTINT2	204
Method getInstance	204
Method destruct	204
Method toString	204
Class CreateWebSettings	205
Var \$ xml	205
Constructor construct	205
Method generateWebSettings	205
Method getInstance	206
Method destruct	206
Method toString	206
Class CreateXlsx	206
Constructor construct	207
Method addSharedStrings	207
Method addSheet	207
Method addTable	208
Method createXlsx	208
Method getInstance	208
Method destruct	208
Method toString	209
Class TransformDoc	209
Class Constant SCHEMA_IMAGEDOCUMENT	209
Class Constant SCHEMA_OFFICEDOCUMENT	209
Constructor construct	209
Method absoluteZipPath	210
Method cleanXHTML	210
Method generatePDF	210
Method generateXHTML	210
Method getFileName	211
Method getstrFile	211
Method getStrOutputFile	211
Method getStrXHTML	211
Method setstrFile	211
Method setStrOutputFile	212
Method setStrXHTML	212
Method validatorXHTML	212
Method destruct	213
Package loader Procedural Elements	215
AutoLoader.inc	215
Package loader Classes	216
Class AutoLoader	216
Method load	216
Method loadPDF	216
Appendices	218
Appendix A - Class Trees	219
elements	219
loader	220

Package create Procedural Elements

CreateDocx.inc

Generate a DOCX file

- **Package** create
- **Version** 2.2
- **Copyright** Copyright (c) 2009-2011 Narcea Producciones Multimedia S.L.
(<http://www.2mdc.com>)
- **Link** <http://www.phpdocx.com>
- **Since** File available since Release 1.0
- **License** LGPL

```
require_once dirname(__FILE__).'/AutoLoader.inc' [line 18]
```

Package create Classes

Class CreateDocx

[line 33]

Main class. Methods and vars to generate a DOCX file

- **Package** create
- **Version** 2.2
- **Copyright** Copyright (c) 2009-2011 Narcea ProduCiones Multimedia S.L.
(<http://www.2mdc.com>)
- **Link** <http://www.phpdocx.com>
- **Since** Class available since Release 1.0
- **License** http://www.phpdocx.com/wp-content/themes/lightword/pro_license.php

CreateDocx::NAMESPACEWORD

= 'w' *[line 35]*

CreateDocx::SCHEMA_IMAGEDOCUMENT

=
'http://schemas.openxmlformats.org/officeDocument/2006/relationships/image' *[line 36]*

CreateDocx::SCHEMA_OFFICEDOCUMENT

=
'http://schemas.openxmlformats.org/officeDocument/2006/relationships/officeDocument' *[line 38]*

CreateDocx::\$fileGraphicTemplate

array = [line 59]

- **Access** public

CreateDocx::\$graphicTemplate

string = [line 53]

- **Access** public

CreateDocx::\$intIdWord

int = [line 47]

- **Static**
- **Access** public

CreateDocx::\$log

Logger = [line 66]

- **Static**
- **Access** public

Constructor *void* function CreateDocx::__construct([\$extension = 'docx']) [line 359]

Function Parameters:

- *string* **\$extension** File extension. Optional, docx as default

Construct

- **Access** public

void function CreateDocx::addBreak([\$type = "]) [*line 726*]

Function Parameters:

- *string* **\$type** Break type Values: 'line', 'page'

Add a break

- **Access** public

void function CreateDocx::addFont(\$fonts) [*line 739*]

Function Parameters:

- *array* **\$fonts** Fonts to add

Add a new font

- **Access** public

void function CreateDocx::addFooter([\$dat = "], [\$paramsFooter = "]) [*line 754*]

Function Parameters:

- *string* **\$dat** Text to add
- *array* **\$paramsFooter** Parameters of footer Values: 'pager' (true, false), 'pagerAlignment' (left, right, false)

Add a footer

- **Access** public

void function CreateDocx::addGraphic(\$dats) [*line 781*]

Function Parameters:

- *array* **\$dats** Parameters of graphic Values: 'color' (1, 2, 3...), 'cornerP' (20, 30...), 'cornerX' (20, 30...), 'cornerY' (20, 30...), 'data' (array of values), 'font' (Arial, Times New Roman...), 'groupBar' (clustered, stacked), 'jc' (center, left, right), 'showPercent' (0, 1), 'sizeX' (10, 11, 12...), 'sizeY' (10, 11, 12...), 'textWrap' (0 (inline), 1 (square), 2 (front), 3 (back), 4 (up and bottom), 5 (clear)), 'title', 'type' (pieChart, barChart, colChart)

Add a graphic

- **Access** public

void function CreateDocx::addHeader([\$text = 'Header'], [\$paramsHeader = ""]) [*line 849*]

Function Parameters:

- *string* **\$text** Text to add
- *array* **\$paramsHeader** Parameters of header

Add a header.

- **Access** public

void function CreateDocx::addImage([\$dats = ""]) [*line 874*]

Function Parameters:

- *array* **\$dats** Image to add and paramaters to use Values: 'border'(1, 2, 3...),

'borderDiscontinuous' (0, 1), 'font' (Arial, Times New Roman...), 'jc' (center, left, right), 'name', 'scaling' (50, 100), 'sizeX' (10, 11, 12...), 'sizeY' (10, 11, 12...), spacingTop (10, 11...), spacingBottom (10, 11...), spacingLeft (10, 11...), spacingRight (10, 11...), 'textWrap' (0 (inline), 1 (square), 2 (front), 3 (back), 4 (up and bottom), 5 (clear))

Add an image

- **Access** public

void function CreateDocx::addLink([\$text = "], [\$textLink = "], [\$font = "], \$link) [*line 933*]

Function Parameters:

- *string* **\$text** Text to use as link
- *string* **\$link** URL link
- *string* **\$font** Type of font Values: 'Arial', 'Times New Roman'...
- **\$textLink**

Add a link

- **Access** public

void function CreateDocx::addList(\$dats, [\$paramsList = "]) [*line 949*]

Function Parameters:

- *array* **\$dats** Values of the list
- *array* **\$paramsList** Parameters to use Values: 'font' (Arial, Times New Roman...), 'val' (0 (clear), 1 (inordinate), 2(numerical))

Add a list

- **Access** public

void function CreateDocx::addMathDocx(\$path) [*line 962*]

Function Parameters:

- *string* **\$path** Path to a file with math eq

Convert a math eq to DOCX

- **Access** public

void function CreateDocx::addMathEq(\$eq) [*line 978*]

Function Parameters:

- *string* **\$eq** Math eq

Add an existing math eq to DOCX

- **Access** public

void function CreateDocx::addParagraph(\$text, [\$style = "], [\$align = "]) [*line 993*]

Function Parameters:

- *string* **\$text** Text to add
- *string* **\$style** Style of the paragraph
- *string* **\$align** Align of the paragraph

Add a paragraph

- **Deprecated**
- **Access** public

void function CreateDocx::addTable(\$dats, [\$parameters = "]) [line 1013]

Function Parameters:

- *array* **\$dats** Values to add
- *array* **\$parameters** Parameters to use Values: 'border' (none, single, double), 'border_color' (ffffff, ff0000), 'border_spacing' (0, 1, 2...), 'border_sz' (10, 11...), 'font' (Arial, Times New Roman...), 'jc' (center, left, right), 'size_col' (1200, 1300...), 'TBLSTYLEval' (Cuadr culamedia3-nfasis1, Sombreadomedia1, Tablaconcuadrucula, TableGrid)

Add a table.

- **Access** public

void function CreateDocx::addTableContents([\$font = "]) [line 1027]

Function Parameters:

- *string* **\$font** Set font type Values: 'Arial', 'Times New Roman'...

Add a table of contents (TOC)

- **Access** public

void function CreateDocx::addText(\$value, [\$style = "]) [line 1047]

Function Parameters:

- *mixed* **\$value** Text or array of texts to add
- *array* **\$style** Style of text Values: 'b' (single), 'color' (ffffff, ff0000...), 'font' (Arial, Times New Roman...), 'i' (single), 'jc' (both, center, distribute, left, right), 'pageBreakBefore' (on, off), 'sz' (1, 2, 3...), 'u' (dash, dotted, double, single, wave, words), 'widowControl' (on, off), 'wordWrap' (on, off)

Add a text

- **Access public**

void function CreateDocx::addTitle(\$text, [\$style = ""]) [*line 1067*]

Function Parameters:

- *string* **\$text** Text to add
- *array* **\$style** Style of title Values: 'b' (single), 'color' (ffffff, ff0000...), 'font' (Arial, Times New Roman...), 'i' (single), 'jc' (both, center, distribute, left, right), 'pageBreakBefore' (on, off), 'sz' (1, 2, 3...), 'u' (dash, dotted, double, single, wave, words), 'widowControl' (on, off), 'wordWrap' (on, off)

Add a title

- **Access public**

void function CreateDocx::createDocx(\$args[0], \$args[1]) [*line 1084*]

Function Parameters:

- *string* **\$args[0]** File name
- *string* **\$args[1]** Page style Values: 'bottom' (4000, 4001...), 'left' (4000, 4001...), 'orient' (landscape), 'right' (4000, 4001), 'titlePage' (1), 'top' (4000, 4001)

Generate a new DOCX file

- **Access** public

void function CreateDocx::fAddBreak([\$type = ""]) [*line 1259*]

Function Parameters:

- *string* **\$type** Break type

Add a break

- **Deprecated**
- **Access** public

void function CreateDocx::fAddFont(\$fonts) [*line 1273*]

Function Parameters:

- *array* **\$fonts** Fonts to add

Add a new font

- **Deprecated**
- **Access** public

void function CreateDocx::fAddFooter([\$dat = "], [\$paramsFooter = "]) [*line 1288*]

Function Parameters:

- *string* **\$dat** Text to add
- *array* **\$paramsFooter** Parameters of footer

Add a footer

- **Deprecated**
- **Access** public

void function CreateDocx::fAddGraphic(\$dats) [line 1309]

Function Parameters:

- *array* **\$dats** Parameters of graphic

Add a graphic

- **Deprecated**
- **Access** public

void function CreateDocx::fAddHeader([\$text = 'Header'], [\$paramsHeader = '']) [line 1378]

Function Parameters:

- *string* **\$text** Text to add
- *array* **\$paramsHeader** Parameters of header

Add a header.

- **Deprecated**
- **Access** public

void function CreateDocx::fAddImage([\$dats = '']) [line 1397]

Function Parameters:

- **array \$dats** Image to add and paramaters to use

Add an image

- **Deprecated**
- **Access** public

void function CreateDocx::fAddLink([\$text = "], [\$textLink = "], [\$font = "], \$link) [line 1456]

Function Parameters:

- *string* **\$text** Text to use as link
- *string* **\$link** URL link
- *string* **\$font** Type of font
- **\$textLink**

Add a link

- **Deprecated**
- **Access** protected

void function CreateDocx::fAddList(\$dats, [\$paramsList = "]) [line 1471]

Function Parameters:

- *array* **\$dats** Values of the list
- *array* **\$paramsList** Parameters to use

Add a list

- **Deprecated**
- **Access** public

void function CreateDocx::fAddMathDocx(\$path) [*line 1485*]

Function Parameters:

- *string* **\$path** Path to a file with math eq

Convert a math eq to DOCX

- **Deprecated**
- **Access** public

void function CreateDocx::fAddMathEq(\$eq) [*line 1502*]

Function Parameters:

- *string* **\$eq** Math eq

Add an existing math eq to DOCX

- **Deprecated**
- **Access** public

void function CreateDocx::fAddParagraph(\$text, [\$style = "], [\$align = "]) [*line 1517*]

Function Parameters:

- *string* **\$text** Text to add
- *string* **\$style** Style of the paragraph
- *string* **\$align** Align of the paragraph

Add a paragraph

- **Deprecated**
- **Access** public

void function CreateDocx::fAddTable(\$dats, [\$parameters = ""]) [*line 1532*]

Function Parameters:

- *array* **\$dats** Values to add
- *array* **\$parameters** Parameters to use

Add a table.

- **Deprecated**
- **Access** public

void function CreateDocx::fAddTableContents([\$font = ""]) [*line 1546*]

Function Parameters:

- *string* **\$font** Set font type

Add a table of contents (TOC)

- **Deprecated**
- **Access** public

void function CreateDocx::fAddText(\$value, [\$style = ""]) [*line 1561*]

Function Parameters:

- *mixed* **\$value** Text or array of texts to add
- *array* **\$style** Style of text

Add a text

- **Deprecated**
- **Access** public

void function CreateDocx::fAddTitle(\$text, [\$style = ""]) [*line 1576*]

Function Parameters:

- *string* **\$text** Text to add
- *array* **\$style** Style of title

Add a title

- **Deprecated**
- **Access** public

void function CreateDocx::fCreateDocx(\$args[0]) [*line 1590*]

Function Parameters:

- *string* **\$args[0]** File name

Generate a new DOCX file

- **Deprecated**
- **Access** public

void function CreateDocx::fSetDefaultFont(\$font) [*line 1732*]

Function Parameters:

- *string* **\$font** The new font

Change the default font

- **Deprecated**
- **Access** public

void function CreateDocx::getXmlContentTypes() [*line 454*]

Getter

- **Access** public

void function CreateDocx::getXmlDocPropsApp() [*line 494*]

Getter

- **Access** public

void function CreateDocx::getXmlDocPropsCore() [*line 514*]

Getter

- **Access** public

void function CreateDocx::getXmlRels_Rels() [*line 474*]

Getter

- **Access** public

void function CreateDocx::getXmlWordDocumentContent() [*line 534*]

Getter

- **Access** public

void function CreateDocx::getXmlWordEndnotes() [*line 554*]

Getter

- **Access** public

void function CreateDocx::getXmlWordFontTable() [*line 574*]

Getter

- **Access** public

void function CreateDocx::getXmlWordFooter1() [*line 594*]

Getter

- **Access** public

void function CreateDocx::getXmlWordHeader1() [*line 614*]

Getter

- **Access** public

void function CreateDocx::getXmlWordRelsDocumentRels() [*line 634*]

Getter

- **Access** public

void function CreateDocx::getXmlWordSettings() [*line 654*]

Getter

- **Access** public

void function CreateDocx::getXmlWordStyles() [*line 674*]

Getter

- **Access** public

void function CreateDocx::getXmlWordThemeTheme1() [line 694]

Getter

- **Access public**

void function CreateDocx::getXmlWordWebSettings() [line 714]

Setter

- **Access public**

void function CreateDocx::setDefaultFont(\$font) [line 1225]

Function Parameters:

- *string* **\$font** The new font Values: 'Arial', 'Times New Roman'...

Change the default font

- **Access public**

void function CreateDocx::setEncodeUTF8() [line 1235]

Transform to UTF-8 charset

- **Access public**

void function CreateDocx::setLanguage([\$lang = 'en-US']) [line 1245]

Function Parameters:

- *\$lang* **\$lang** Locale: en-US, es-ES...

Change default language.

- **Access public**

void function CreateDocx::setXmlContentTypes(\$xmlContentTypes) [line 444]

Function Parameters:

- **\$xmlContentTypes**

Setter

- **Access public**

void function CreateDocx::setXmlDocPropsApp(\$xmlDocPropsApp) [line 484]

Function Parameters:

- **\$xmlDocPropsApp**

Setter

- **Access public**

void function CreateDocx::setXmlDocPropsCore(\$xmlDocPropsCore) [line 504]

Function Parameters:

- **\$xmlDocPropsCore**

Setter

- **Access public**

void function CreateDocx::setXmlRelsRels(\$xmlRelsRels) [line 464]

Function Parameters:

- **\$xmlRelsRels**

Setter

- **Access public**

void function CreateDocx::setXmlWordDocument(\$xmlWordDocument) [line 524]

Function Parameters:

- **\$xmlWordDocument**

Setter

- **Access public**

void function CreateDocx::setXmlWordEndnotes(\$xmlWordEndnotes) [line 544]

Function Parameters:

- **\$xmlWordEndnotes**

Setter

- **Access public**

void function CreateDocx::setXmlWordFontTable(\$xmlWordFontTable) [line 564]

Function Parameters:

- **\$xmlWordFontTable**

Setter

- **Access public**

void function CreateDocx::setXmlWordFooter1(\$xmlWordFooter) [line 584]

Function Parameters:

- **\$xmlWordFooter**

Setter

- **Access** public

void function CreateDocx::setXmlWordHeader1(\$xmlWordHeader) [*line 604*]

Function Parameters:

- **\$xmlWordHeader**

Setter

- **Access** public

void function CreateDocx::setXmlWordRelsDocumentRels(\$xmlWordRelsDocumentRels) [*line 624*]

Function Parameters:

- **\$xmlWordRelsDocumentRels**

Setter

- **Access** public

void function CreateDocx::setXmlWordSettings(\$xmlWordSettings) [*line 644*]

Function Parameters:

- **\$xmlWordSettings**

Setter

- **Access** public

void function CreateDocx::setXmlWordStyles(\$xmlWordStyles) [line 664]

Function Parameters:

- **\$xmlWordStyles**

Setter

- **Access** public

void function CreateDocx::setXmlWordThemeTheme1(\$xmlWordThemeTheme) [line 684]

Function Parameters:

- **\$xmlWordThemeTheme**

Setter

- **Access** public

void function CreateDocx::setXmlWordWebSettings(\$xmlWordWebSettings) [line 704]

Function Parameters:

- **\$xmlWordWebSettings**

Setter

- **Access** public

void function CreateDocx::__destruct() [*line 422*]

Destruct

- **Access** public

string function CreateDocx::__toString() [*line 433*]

Magic method, returns current word XML

- **Access** public

Package elements Procedural Elements

CreateChartRels.inc

Create relationships used by images, charts...

- **Package** elements
- **Version** 1.0
- **Copyright** Copyright (c) 2009-2011 Narcea Producciones Multimedia S.L.
(<http://www.2mdc.com>)
- **Link** <http://www.phpdocx.com>
- **Since** File available since Release 1.0
- **License** LGPL

```
include_once dirname(__FILE__).'/CreateElement.inc' [line 15]
```

CreateElement.inc

Create tag elements

- **Package** elements
- **Version** 1.0
- **Copyright** Copyright (c) 2009-2011 Narcea Producciones Multimedia S.L.
(<http://www.2mdc.com>)
- **Link** <http://www.phpdocx.com>
- **Since** File available since Release 1.0
- **License** LGPL

CreateExcelSharedStrings.inc

Generate excel shared strings

- **Package** elements
- **Version** 1.0
- **Copyright** Copyright (c) 2009-2011 Narcea Producciones Multimedia S.L.
(<http://www.2mdc.com>)
- **Link** <http://www.phpdocx.com>
- **Since** File available since Release 1.0
- **License** LGPL

```
include_once dirname(__FILE__).'/CreateElement.inc' [line 15]
```

CreateExcelSheet.inc

Create excel sheet

- **Package** elements
- **Version** 1.0
- **Copyright** Copyright (c) 2009-2011 Narcea Producciones Multimedia S.L.
(<http://www.2mdc.com>)
- **Link** <http://www.phpdocx.com>
- **Since** File available since Release 1.0
- **License** LGPL

```
include_once dirname(__FILE__).'/CreateElement.inc' [line 15]
```

CreateExcelTable.inc

Create excel table

- **Package** elements
- **Version** 1.0
- **Copyright** Copyright (c) 2009-2011 Narcea Producciones Multimedia S.L.
(<http://www.2mdc.com>)
- **Link** <http://www.phpdocx.com>
- **Since** File available since Release 1.0
- **License** LGPL

```
include_once dirname(__FILE__).'/CreateElement.inc' [line 15]
```


CreateFontTable.inc

Create font table

- **Package** elements
- **Version** 1.0
- **Copyright** Copyright (c) 2009-2011 Narcea Producciones Multimedia S.L.
(<http://www.2mdc.com>)
- **Link** <http://www.phpdocx.com>
- **Since** File available since Release 1.0
- **License** LGPL

```
include_once dirname(__FILE__).'/CreateElement.inc' [line 15]
```

CreateFooter.inc

Create footer

- **Package** elements
- **Version** 1.0
- **Copyright** Copyright (c) 2009-2011 Narcea Producciones Multimedia S.L.
(<http://www.2mdc.com>)
- **Link** <http://www.phpdocx.com>
- **Since** File available since Release 1.0
- **License** LGPL

```
include_once dirname(__FILE__).'/CreateElement.inc' [line 15]
```

CreateFootnote.inc

Create footnote

- **Package** elements
- **Version** 1.0
- **Copyright** Copyright (c) 2009-2011 Narcea Producciones Multimedia S.L.
(<http://www.2mdc.com>)
- **Link** <http://www.phpdocx.com>
- **Since** File available since Release 1.0
- **License** LGPL

```
include_once dirname(__FILE__).'/CreateElement.inc' [line 15]
```

CreateGraphic.inc

Create graphics (charts)

- **Package** elements
- **Version** 2.2
- **Copyright** Copyright (c) 2009-2011 Narcea Producciones Multimedia S.L.
(<http://www.2mdc.com>)
- **Link** <http://www.phpdocx.com>
- **Since** File available since Release 1.0
- **License** LGPL

```
include_once dirname(__FILE__).'/CreateElement.inc' [line 15]
```

CreateHeader.inc

Create header

- **Package** elements
- **Version** 1.0
- **Copyright** Copyright (c) 2009-2011 Narcea Producciones Multimedia S.L.
(<http://www.2mdc.com>)
- **Link** <http://www.phpdocx.com>
- **Since** File available since Release 1.0
- **License** LGPL

```
include_once dirname(__FILE__).'/CreateElement.inc' [line 15]
```

CreteImage.inc

Create images

- **Package** elements
- **Version** 1.0
- **Copyright** Copyright (c) 2009-2011 Narcea Producciones Multimedia S.L.
(<http://www.2mdc.com>)
- **Link** <http://www.phpdocx.com>
- **Since** File available since Release 1.0
- **License** LGPL

```
include_once dirname(__FILE__).'/CreateElement.inc' [line 15]
```

CreateLink.inc

Create links using text strings

- **Package** elements
- **Version** 1.0
- **Copyright** Copyright (c) 2009-2011 Narcea Producciones Multimedia S.L.
(<http://www.2mdc.com>)
- **Link** <http://www.phpdocx.com>
- **Since** File available since Release 1.0
- **License** LGPL

```
include_once dirname(__FILE__).'/CreateElement.inc' [line 15]
```

CreateList.inc

Create lists

- **Package** elements
- **Version** 1.0
- **Copyright** Copyright (c) 2009-2011 Narcea Producciones Multimedia S.L.
(<http://www.2mdc.com>)
- **Link** <http://www.phpdocx.com>
- **Since** File available since Release 1.0
- **License** LGPL

```
include_once dirname(__FILE__).'/CreateElement.inc' [line 15]
```


CreatePage.inc

Create pages

- **Package** elements
- **Version** 1.0
- **Copyright** Copyright (c) 2009-2011 Narcea Producciones Multimedia S.L.
(<http://www.2mdc.com>)
- **Link** <http://www.phpdocx.com>
- **Since** File available since Release 1.0
- **License** LGPL

```
include_once dirname(__FILE__).'/CreateElement.inc' [line 15]
```

CreateSettings.inc

Create default settings

- **Package** elements
- **Version** 1.0
- **Copyright** Copyright (c) 2009-2011 Narcea Producciones Multimedia S.L.
(<http://www.2mdc.com>)
- **Link** <http://www.phpdocx.com>
- **Since** File available since Release 1.0
- **License** LGPL

```
include_once dirname(__FILE__).'/CreateElement.inc' [line 15]
```

CreateStyle.inc

Create styles

- **Package** elements
- **Version** 2.1
- **Copyright** Copyright (c) 2009-2011 Narcea Producciones Multimedia S.L.
(<http://www.2mdc.com>)
- **Link** <http://www.phpdocx.com>
- **Since** File available since Release 1.0
- **License** LGPL

```
include_once dirname(__FILE__).'/CreateElement.inc' [line 16]
```

CreateStyleTable.inc

Create style table

- **Package** elements
- **Version** 1.0
- **Copyright** Copyright (c) 2009-2011 Narcea Producciones Multimedia S.L.
(<http://www.2mdc.com>)
- **Link** <http://www.phpdocx.com>
- **Since** File available since Release 1.0
- **License** LGPL

```
include_once dirname(__FILE__).'/CreateElement.inc' [line 15]
```

CreateTable.inc

Create tables

- **Package** elements
- **Version** 1.0
- **Copyright** Copyright (c) 2009-2011 Narcea Producciones Multimedia S.L.
(<http://www.2mdc.com>)
- **Link** <http://www.phpdocx.com>
- **Since** File available since Release 1.0
- **License** LGPL

```
include_once dirname(__FILE__).'/CreateElement.inc' [line 15]
```

CreateTableContents.inc

Create table of contents

- **Package** elements
- **Version** 1.0
- **Copyright** Copyright (c) 2009-2011 Narcea Producciones Multimedia S.L.
(<http://www.2mdc.com>)
- **Link** <http://www.phpdocx.com>
- **Since** File available since Release 1.0
- **License** LGPL

```
include_once dirname(__FILE__).'/CreateElement.inc' [line 15]
```

CreateText.inc

Create text

- **Package** elements
- **Version** 1.0
- **Copyright** Copyright (c) 2009-2011 Narcea Producciones Multimedia S.L.
(<http://www.2mdc.com>)
- **Link** <http://www.phpdocx.com>
- **Since** File available since Release 1.0
- **License** LGPL

```
include_once dirname(__FILE__).'/CreateElement.inc' [line 15]
```

CreateTheme1.inc

- **Package** elements
- **Version** 1.0
- **Copyright** Copyright (c) 2009-2011 Narcea Producciones Multimedia S.L.
(<http://www.2mdc.com>)
- **Link** <http://www.phpdocx.com>
- **Since** File available since Release 1.0
- **License** LGPL

`include_once dirname(__FILE__).'/CreateElement.inc' [line 15]`

CreateWebSettings.inc

Create default websettings XML

- **Package** elements
- **Version** 1.0
- **Copyright** Copyright (c) 2009-2011 Narcea Producciones Multimedia S.L.
(<http://www.2mdc.com>)
- **Link** <http://www.phpdocx.com>
- **Since** File available since Release 1.0
- **License** LGPL

```
include_once dirname(__FILE__).'/CreateElement.inc' [line 15]
```

CreateXlsx.inc

Create XLSX

- **Package** elements
- **Version** 1.0
- **Copyright** Copyright (c) 2009-2011 Narcea Producciones Multimedia S.L.
(<http://www.2mdc.com>)
- **Link** <http://www.phpdocx.com>
- **Since** File available since Release 1.0
- **License** LGPL

TransformDoc.inc

Transform DOCX to PDF or XHTML

- **Package** elements
- **Version** 1.0
- **Copyright** Copyright (c) 2009-2011 Narcea Producciones Multimedia S.L.
(<http://www.2mdc.com>)
- **Link** <http://www.phpdocx.com>
- **Since** File available since Release 1.0
- **License** LGPL

`require_once dirname(__FILE__).'/AutoLoader.inc'` [*line 18*]

Package elements Classes

Class CreateChartRels

[line 29]

Create relationships used by images, charts...

- **Package** elements
- **Version** 1.0
- **Copyright** Copyright (c) 2009-2011 Narcea Producciones Multimedia S.L. (<http://www.2mdc.com>)
- **Link** <http://www.phpdocx.com>
- **Since** Class available since Release 1.0
- **License** http://www.phpdocx.com/wp-content/themes/lightword/pro_license.php

CreateChartRels::\$_xml

mixed = [line 36]

- **Access** protected

Constructor *void* function CreateChartRels::__construct() [line 49]

Construct

- **Access** public

void function CreateChartRels::createRelationship(\$idChart) [line 95]

Function Parameters:

- *int* **\$idChart**

Create relationship document to use in DOCX file

- **Access** public

void function CreateChartRels::generateRELATIONSHIP(\$idChart, [\$id = 1], \$id.) [line 109]

Function Parameters:

- *int* **\$idChart**
- *int* **\$id**. Optional, use 1 as default
- **\$id**

New relationship, added to relationships XML

- **Access** protected

void function CreateChartRels::generateRELATIONSHIPS() [line 126]

Main tags of relationships XML

- **Access** protected

CreateChartRels function `CreateChartRels::getInstance()` [*line 81*]

Singleton, return instance of class

- **Static**
- **Access** public

void function `CreateChartRels::__destruct()` [*line 59*]

Destruct

- **Access** public

string function `CreateChartRels::__toString()` [*line 70*]

Magic method, returns current XML

- **Access** public

Class CreateElement

[*line 28*]

Main class, create tag elements

- **Package** elements
- **Version** 1.0
- **Copyright** Copyright (c) 2009-2011 Narcea Producciones Multimedia S.L.
(<http://www.2mdc.com>)
- **Link** <http://www.phpdocx.com>

- **Since Class** available since Release 1.0
- **License** http://www.phpdocx.com/wp-content/themes/lightword/pro_license.php

CreateElement::MATHNAMESPACEWORD

= 'm' [*line 30*]

CreateElement::NAMESPACEWORD

= 'w' [*line 31*]

CreateElement::\$_xml

string = [*line 38*]

- **Access** protected

Constructor *void* function CreateElement::__construct() [*line 45*]

Construct

- **Access** public

void function CreateElement::cleanTemplate() [*line 851*]

Delete pending tags

- **Access** protected

void function CreateElement::cleanTemplateFirstRPR() [*line 861*]

Delete first w:rpr

- **Access** protected

void function CreateElement::generateANCHOR([\$behindDoc = 0], [\$distT = '0'], [\$distB = '0'], [\$distL = '114300'], [\$distR = '114300'], [\$simplePos = 0], [\$relativeHeight = '251658240'], [\$locked = 0], [\$layoutInCell = 1], [\$allowOverlap = 1]) [*line 257*]

Function Parameters:

- *string* **\$behindDoc**
- *string* **\$distT**
- *string* **\$distB**
- *string* **\$distL**
- *string* **\$distR**
- *int* **\$simplePos**
- *string* **\$relativeHeight**
- *string* **\$locked**
- *string* **\$layoutInCell**
- *string* **\$allowOverlap**

Generate w:anchor

- **Access** protected

void function CreateElement::generateAVLST() [*line 778*]

Generate w:avlst

- **Access** protected

void function CreateElement::generateB([\$strVal = 'single'], \$val) [*line 144*]

Function Parameters:

- *string* **\$val**
- **\$strVal**

Generate w:b

- **Access** protected

void function CreateElement::generateBCS() [*line 157*]

Generate w:bcS

- **Access** protected

void function CreateElement::generateBLIP([\$cstate = 'print']) [*line 656*]

Function Parameters:

- *string* **\$cstate**

Generate w:blip

- **Access** protected

void function CreateElement::generateBLIPFILL() [*line 641*]

Generate w:blipfill

- **Access** protected

void function CreateElement::generateCNVGRAPHICFRAMEPR() [*line 510*]

Generate w:cnvgraphicframepr

- **Access** protected

void function CreateElement::generateCNVPICPR() [*line 627*]

Generate w:cnvpicpr

- **Access** protected

void function CreateElement::generateCNVPR([\$id = '0']) [*line 612*]

Function Parameters:

- *string* **\$id**

Generate w:cnvpr

- **Access** protected

void function CreateElement::generateDOCPR([\$id = "1"], [\$name = "0 Imagen"]) [*line 495*]

Function Parameters:

- *string* **\$id**
- *string* **\$name**

Generate w:docpr

- **Access** protected

void function CreateElement::generateDRAWING() [*line 211*]

Generate w:drawing

- **Access** protected

void function CreateElement::generateEFFECTEXTENT([\$l = "19050"], [\$t = "0"], [\$r = "4307"], [\$b = "0"]) [*line 366*]

Function Parameters:

- *string* **\$l**
- *string* **\$t**
- *string* **\$r**
- *string* **\$b**

Generate w:effectextent

- **Access** protected

void function CreateElement::generateEXT([\$cx = '2997226'], [\$cy = '2247918']) [*line 747*]

Function Parameters:

- *string* **\$cx**
- *string* **\$cy**

Generate w:ext

- **Access** protected

void function CreateElement::generateEXTENT([\$cx = '2986543'], [\$cy = '2239906']) [*line 348*]

Function Parameters:

- *string* **\$cx**
- *string* **\$cy**

Generate w:extent

- **Access** protected

void function CreateElement::generateFILLRECT() [*line 686*]

Generate w:fillrect

- **Access** protected

void function CreateElement::generateGRAPHIC([\$xmlns = 'http://schemas.openxmlformats.org/drawingml/2006/main']) [*line 547*]

Function Parameters:

- *string* **\$xmlns**

Generate w:graphic

- **Access** protected

void function CreateElement::generateGRAPHICDATA([\$uri = 'http://schemas.openxmlformats.org/drawingml/2006/picture']) [*line 564*]

Function Parameters:

- *string* \$uri

Generate w:graphicdata

- Access protected

void function CreateElement::generateGRAPHICPRAMELOCKS([\$noChangeAspect = ""]) [*line 526*]

Function Parameters:

- *string* \$noChangeAspect

Generate w:graphicframelocks

- Access protected

void function CreateElement::generateINLINE([\$distT = '0'], [\$distB = '0'], [\$distL = '0'], [\$distR = '0']) [*line 230*]

Function Parameters:

- *string* \$distT
- *string* \$distB
- *string* \$distL
- *string* \$distR

Generate w:inline

- **Access** protected

void function CreateElement::generateJC([\$val = "]) [*line 129*]

Function Parameters:

- *string* **\$val**

Generate w:jc

- **Access** protected

void function CreateElement::generateLINETO([\$x = '-198'], [\$y = '21342']) [*line 478*]

Function Parameters:

- *string* **\$x**
- *string* **\$y**

Generate w:lineto

- **Access** protected

void function CreateElement::generateLN([\$w = '12700']) [*line 793*]

Function Parameters:

- *string* **\$w**

Generate w:ln

- **Access** protected

void function CreateElement::generateNOPROOF() [*line 171*]

Generate w:noproof

- **Access** protected

void function CreateElement::generateNVPICPR() [*line 597*]

Generate w:nvpicpr

- **Access** protected

void function CreateElement::generateOFF([\$x = '0'], [\$y = '0']) [*line 730*]

Function Parameters:

- *string* \$x
- *string* \$y

Generate w:off

- **Access** protected

void function CreateElement::generateP() [*line 75*]

Generate w:p

- **Access** protected

void function CreateElement::generatePIC([\$pic = 'http://schemas.openxmlformats.org/drawingml/2006/picture']) *[line 581]*

Function Parameters:

- *string* **\$pic**

Generate w:pic

- **Access** protected

void function CreateElement::generatePOSITIONH([\$relativeFrom = 'column']) *[line 301]*

Function Parameters:

- *string* **\$relativeFrom**

Generate w:positionh

- **Access** protected

void function CreateElement::generatePOSITIONV([\$relativeFrom = 'paragraph']) *[line 317]*

Function Parameters:

- *string* **\$relativeFrom**

Generate w:positionv

- **Access** protected

void function CreateElement::generatePOSOFFSET(\$num) [*line 333*]

Function Parameters:

- *int* \$num

Generate w:posoffset

- **Access** protected

void function CreateElement::generatePPR() [*line 87*]

Generate w:ppr

- **Access** protected

void function CreateElement::generatePRSTDASH([\$val = 'sysDash']) [*line 837*]

Function Parameters:

- *string* \$val

Generate w:prstdash

- **Access** protected

void function CreateElement::generatePRSTGEOM([\$prst = 'rect']) [*line 763*]

Function Parameters:

- *string* **\$prst**

Generate w:prstgeom

- **Access** protected

void function CreateElement::generatePSTYLE([\$val = 'Textonotaalfinal']) [*line 884*]

Function Parameters:

- *string* **\$val**

Generate w:pstyle

- **Access** protected

void function CreateElement::generateQUITAR() [*line 871*]

Generate w:r

- **Access** protected

void function CreateElement::generateR() [*line 185*]

Generate w:r

- **Access** protected

void function CreateElement::generateRFONTS(\$font) [*line 917*]

Function Parameters:

- *string* **\$font**

Generate w:rfonts

- **Access** protected

void function CreateElement::generateRPR() [*line 114*]

Generate w:rpr

- **Access** protected

void function CreateElement::generateRSTYLE([\$val = 'Refdenotaalfinal']) [*line 900*]

Function Parameters:

- *string* **\$val**

Generate w:rstyle

- **Access** protected

void function CreateElement::generateSCHEMECLR([\$val = 'tx1']) [*line 823*]

Function Parameters:

- *string* \$val

Generate w:schemeclr

- **Access** protected

void function CreateElement::generateSIMPLEPOS([\$x = '0'], [\$y = '0']) [*line 285*]

Function Parameters:

- *string* \$x
- *string* \$y

Generate w:simplepos

- **Access** protected

void function CreateElement::generateSOLIDFILL() [*line 808*]

Generate w:solidfill

- **Access** protected

void function CreateElement::generateSPPR() [line 700]

Generate w:sppr

- **Access** protected

void function CreateElement::generateSTART([\$x = '-198'], [\$y = '0']) [line 460]

Function Parameters:

- *string* **\$x**
- *string* **\$y**

Generate w:start

- **Access** protected

void function CreateElement::generateSTRETCH() [line 672]

Generate w:stretch

- **Access** protected

void function CreateElement::generateT(\$dat) [line 101]

Function Parameters:

- *string* **\$dat**

Generate w:t

- **Access** protected

void function CreateElement::generateWRAPNONE() [*line 398*]

Generate w:wrapnone

- **Access** protected

void function CreateElement::generateWRAPPOLYGON([*\$edited* = '0']) [*line 443*]

Function Parameters:

- *string* ***\$edited***

Generate w:wrappolygon

- **Access** protected

void function CreateElement::generateWRAPSQUARE([*\$wrapText* = "bothSides"]) [*line 383*]

Function Parameters:

- *string* ***\$wrapText***

Generate w:wrapsquare

- **Access** protected

void function CreateElement::generateWRAPTHROUGH([\$wrapText = 'bothSides']) [*line 427*]

Function Parameters:

- *string* **\$wrapText**

Generate w:wrapthrough

- **Access** protected

void function CreateElement::generateWRAPTOPANDBOTTOM() [*line 412*]

Generate w:wraptopandbottom

- **Access** protected

void function CreateElement::generateXFRM() [*line 714*]

Generate w:xfrm

- **Access** protected

void function CreateElement::__destruct() [*line 55*]

Destruct

- **Access** public

string function CreateElement::__toString() [*line 65*]

- **Access** public

Class CreateExcelSharedStrings

[*line 29*]

Generate excel shared strings

- **Package** elements
- **Version** 1.0
- **Copyright** Copyright (c) 2009-2011 Narcea Producciones Multimedia S.L. (<http://www.2mdc.com>)
- **Link** <http://www.phpdocx.com>
- **Since** Class available since Release 1.0
- **License** http://www.phpdocx.com/wp-content/themes/lightword/pro_license.php

Constructor *void* function CreateExcelSharedStrings::__construct() [*line 44*]

Construct

- **Access** public

void function CreateExcelSharedStrings::createExcelSharedStrings(\$args[0], \$args[1]) [*line 89*]

Function Parameters:

- *string* **\$args[0]**
- *string* **\$args[1]**

Create excel shared strings

- **Access** public

void function CreateExcelSharedStrings::generateSI() [*line 155*]

Generate si

- **Access** protected

void function CreateExcelSharedStrings::generateSST(\$num) [*line 142*]

Function Parameters:

- *string* \$num

Generate sst

- **Access** protected

void function CreateExcelSharedStrings::generateT(\$name, [\$space = ""]) [*line 168*]

Function Parameters:

- *string* \$name
- *string* \$space

Generate t

- **Access** protected

CreateExcelSharedStrings function `CreateExcelSharedStrings::getInstance()` [*line 74*]

- **Static**
- **Access** public

void function `CreateExcelSharedStrings::__destruct()` [*line 54*]

Destruct

- **Access** public

string function `CreateExcelSharedStrings::__toString()` [*line 64*]

- **Access** public

Class `CreateExcelSheet` [*line 29*]

Create excel sheet

- **Package** elements
- **Version** 1.0

- **Copyright** Copyright (c) 2009-2011 Narcea Producciones Multimedia S.L. (<http://www.2mdc.com>)
- **Link** <http://www.phpdocx.com>
- **Since** Class available since Release 1.0
- **License** http://www.phpdocx.com/wp-content/themes/lightword/pro_license.php

Constructor *void* function CreateExcelSheet::__construct() [*line 44*]

Construct

- **Access** public

void function CreateExcelSheet::createExcelSheet(\$args[0], \$args[1]) [*line 90*]

Function Parameters:

- *string* **\$args[0]**
- *array* **\$args[1]**

Create excel sheet

- **Access** public

void function CreateExcelSheet::generateC(\$r, \$s, [\$t = ""]) [*line 324*]

Function Parameters:

- *string* **\$r**
- *string* **\$s**
- *string* **\$t**

Generate c

- **Access** protected

void function CreateExcelSheet::generateCOL([\$min = '1'], [\$max = '1'], [\$width = '11.85546875'], [\$customWidth = '1']) [*line 279*]

Function Parameters:

- *string* **\$min**
- *string* **\$max**
- *string* **\$width**
- *string* **\$customWidth**

Generate col

- **Access** protected

void function CreateExcelSheet::generateCOLS() [*line 264*]

Generate cols

- **Access** protected

void function CreateExcelSheet::generateDIMENSION(\$sizeX, \$sizeY) [*line 187*]

Function Parameters:

- *int* **\$sizeX**
- *int* **\$sizeY**

Generate dimension

- **Access** protected

void function CreateExcelSheet::generatePAGEMARGINS([\$left = '0.7'], [\$righth = '0.7'], [\$bottom = '0.75'], [\$stop = '0.75'], [\$header = '0.3'], [\$footer = '0.3']) *[line 361]*

Function Parameters:

- *string* **\$left**
- *string* **\$righth**
- *string* **\$bottom**
- *string* **\$stop**
- *string* **\$header**
- *string* **\$footer**

Generate pagemargins

- **Access** protected

void function CreateExcelSheet::generatePAGESETUP([\$paperSize = '9'], [\$orientation = 'portrait'], [\$sid = '1']) *[line 381]*

Function Parameters:

- *string* **\$paperSize**
- *string* **\$orientation**
- *string* **\$sid**

Generate pagesetup

- **Access** protected

void function CreateExcelSheet::generateROW(\$r, \$spans) *[line 307]*

Function Parameters:

- *string* **\$r**
- *string* **\$spans**

Generate row

- **Access** protected

void function CreateExcelSheet::generateSELECTION(\$num) [*line 234*]

Function Parameters:

- *string* **\$num**

Generate selection

- **Access** protected

void function CreateExcelSheet::generateSHEETDATA() [*line 293*]

Generate sheetdata

- **Access** protected

void function CreateExcelSheet::generateSHEETFORMATPR([\$baseColWidth = '10'], [\$defaultRowHeight = '15']) [*line 249*]

Function Parameters:

- *string* **\$baseColWidth**
- *string* **\$defaultRowHeight**

Generate sheetformatpr

- **Access** protected

void function CreateExcelSheet::generateSHEETVIEW([\$tabSelected = '1'], [\$workbookViewId = '0']) [*line 218*]

Function Parameters:

- *string* **\$tabSelected**
- *string* **\$workbookViewId**

Generate sheetview

- **Access** protected

void function CreateExcelSheet::generateSHEETVIEWS() [*line 204*]

Generate sheetviews

- **Access** protected

void function CreateExcelSheet::generateTABLEPART([\$id = '1']) [*line 411*]

Function Parameters:

- *string* **\$id**

Generate tablepart

- **Access** protected

void function CreateExcelSheet::generateTABLEPARTS([\$count = '1']) [*line 397*]

Function Parameters:

- *string* **\$count**

Generate tableparts

- **Access** protected

void function CreateExcelSheet::generateV(\$num) [*line 343*]

Function Parameters:

- *string* **\$num**

Generate v

- **Access** protected

void function CreateExcelSheet::generateWORKSHEET() [*line 170*]

Generate worksheet

- **Access** protected

CreateExcelSheet function `CreateExcelSheet::getInstance()` [*line 75*]

- **Static**
- **Access** public

void function `CreateExcelSheet::__destruct()` [*line 54*]

Destruct

- **Access** public

string function `CreateExcelSheet::__toString()` [*line 64*]

- **Access** public

Class `CreateExcelTable`

[*line 29*]

Create excel table

- **Package** elements
- **Version** 1.0
- **Copyright** Copyright (c) 2009-2011 Narcea Producciones Multimedia S.L.
(<http://www.2mdc.com>)
- **Link** <http://www.phpdocx.com>
- **Since** File available since Release 1.0
- **License** http://www.phpdocx.com/wp-content/themes/lightword/pro_license.php

Constructor *void* function CreateExcelTable::__construct() [*line 44*]

Construct

- **Access** public

void function CreateExcelTable::createExcelTable(0, 1) [*line 89*]

Function Parameters:

- *string* 0 args[0]
- *string* 1 args[1]

Create excel table

- **Access** public

void function CreateExcelTable::generateTABLE(\$rows, \$cols) [*line 128*]

Function Parameters:

- *int* \$rows
- *int* \$cols

Generate table

- **Access** protected

void function CreateExcelTable::generateTABLECOLUMN([\$id = '2'], [\$name = '']) [*line 163*]

Function Parameters:

- *string* **\$id**
- *string* **\$name**

Generate tablecolumn

- **Access** protected

void function CreateExcelTable::generateTABLECOLUMNS([\$count = '2']) [*line 148*]

Function Parameters:

- *string* **\$count**

Generate tablecolumns

- **Access** protected

void function CreateExcelTable::generateTABLESTYLEINFO([\$showFirstColumn = '0'], [\$showLastColumn = "0"], [\$showRowStripes = "1"], [\$showColumnStripes = "0"]) [*line 182*]

Function Parameters:

- *string* **\$showFirstColumn**
- *string* **\$showLastColumn**
- *string* **\$showRowStripes**
- *string* **\$showColumnStripes**

Generate tablestyleinfo

- **Access** protected

CreateExcelTable function `CreateExcelTable::getInstance()` [*line 74*]

- **Static**
- **Access** public

void function `CreateExcelTable::__destruct()` [*line 54*]

Destruct

- **Access** public

string function `CreateExcelTable::__toString()` [*line 64*]

- **Access** public

Class `CreateFontTable`

[*line 29*]

Create font table

- **Package** elements
- **Version** 1.0
- **Copyright** Copyright (c) 2009-2011 Narcea Producciones Multimedia S.L. (<http://www.2mdc.com>)
- **Link** <http://www.phpdocx.com>
- **Since** Class available since Release 1.0

- **License** http://www.phpdocx.com/wp-content/themes/lightword/pro_license.php

CreateFontTable::\$_xml

string = [line 36]

- **Access** protected

Constructor *void* function CreateFontTable::__construct() [line 51]

Construct

- **Access** public

void function CreateFontTable::createFont(0) [line 96]

Function Parameters:

- *array* **0** args[0]

Create font

- **Access** public

void function CreateFontTable::generateCHARSET([\$val = '00']) [line 159]

Function Parameters:

- *string* **\$val**

Generate w:charset

- **Access** protected

void function CreateFontTable::generateFAMILY([\$val = 'swiss']) [*line 175*]

Function Parameters:

- *string* **\$val**

Generate w:family

- **Access** protected

void function CreateFontTable::generateFONT([\$name = 'Calibri']) [*line 127*]

Function Parameters:

- *string* **\$name**

Generate w:font

- **Access** protected

void function CreateFontTable::generatePANOSE1([\$val = '020F0502020204030204']) [*line 142*]

Function Parameters:

- *string* **\$val**

Generate w:panose1

- **Access** protected

void function CreateFontTable::generatePITCH([\$val = '00']) [line 192]

Function Parameters:

- *string* **\$val**

Generate w:pitch

- **Access** protected

void function CreateFontTable::generateSIG([\$usbA = 'A00002EF'], [\$usbB = '4000207B'], [\$usbC = '00000000'], [\$usbD = '00000000'], [\$csbA = '0000009F'], [\$csbB = '00000000']) [line 214]

Function Parameters:

- *string* **\$usbA**
- *string* **\$usbB**
- *string* **\$usbC**
- *string* **\$usbD**
- *string* **\$csbA**
- *string* **\$csbB**

Generate w:sig

- **Access** protected

CreateFontTable function `CreateFontTable::getInstance()` [*line 82*]

- **Static**
- **Access** public

void function `CreateFontTable::__destruct()` [*line 61*]

Destruct

- **Access** public

string function `CreateFontTable::__toString()` [*line 71*]

- **Access** public

Class `CreateFooter` [*line 29*]

Create footer

- **Package** elements
- **Version** 1.0
- **Copyright** Copyright (c) 2009-2011 Narcea Producciones Multimedia S.L.
(<http://www.2mdc.com>)
- **Link** <http://www.phpdocx.com>
- **Since** Class available since Release 1.0
- **License** http://www.phpdocx.com/wp-content/themes/lightword/pro_license.php

Constructor *void* function CreateFooter::__construct() [*line 52*]

Construct

- **Access** public

void function CreateFooter::createFooter(0, 1) [*line 98*]

Function Parameters:

- *string* **0** args[0]
- *array* **1** args[1]

Create footer

- **Access** public

void function CreateFooter::generateFLDSIMPLE() [*line 121*]

Generate w:fldsimple

- **Access** protected

void function CreateFooter::generateFTR() [*line 136*]

Generate ftr token

- **Access** protected

void function CreateFooter::generateP() [line 146]

Generate w:p

- **Access** protected

void function CreateFooter::generatePTAB([\$relativeTo = 'margin'], [\$alignment = 'right'], [\$leader = 'none']) [line 162]

Function Parameters:

- *string* **\$relativeTo**
- *string* **\$alignment**
- *string* **\$leader**

Generate w:ptab

- **Access** protected

void function CreateFooter::generateR() [line 183]

Generate w:r

- **Access** protected

CreateFooter function CreateFooter::getInstance() [line 83]

- **Static**
- **Access** public

void function CreateFooter::__destruct() [*line 62*]

Destruct

- **Access** public

string function CreateFooter::__toString() [*line 72*]

- **Access** public

Class CreateFootnote

[*line 29*]

Create footnote

- **Package** elements
- **Version** 1.0
- **Copyright** Copyright (c) 2009-2011 Narcea Producciones Multimedia S.L. (<http://www.2mdc.com>)
- **Link** <http://www.phpdocx.com>
- **Since** Class available since Release 1.0
- **License** http://www.phpdocx.com/wp-content/themes/lightword/pro_license.php

CreateFootnote::\$init

bool = 0 [*line 37*]

- **Static**
- **Access** public

Constructor *void* function CreateFootnote::__construct() [*line 61*]

Construct

- **Access public**

void function CreateFootnote::createDocumentFootnote(\$args[0]) [*line 135*]

Function Parameters:

- *array* **\$args[0]**

Create document footnote

- **Access public**

void function CreateFootnote::createFootnote(\$args[0]) [*line 107*]

Function Parameters:

- *array* **\$args[0]**

Create footnote

- **Access public**

void function CreateFootnote::createInitFootnote(\$args[0]) [*line 162*]

Function Parameters:

- *array* **\$args[0]**

Create init footnote

- **Access public**

void function CreateFootnote::generateFOOTNOTE(\$type) [*line 181*]

Function Parameters:

- *string* **\$type**

Generate w:footnote

- **Access protected**

void function CreateFootnote::generateFOOTNOTEREF() [*line 288*]

Generate w:footnoteref

- **Access protected**

void function CreateFootnote::generateFOOTNOTEREFERENCE([\$id = ""]) [*line 303*]

Function Parameters:

- *string* **\$id**

Generate w:footnotereference

- **Access** protected

void function CreateFootnote::generateP([\$rsidR = '005F02E5'], [\$rsidRDefault = '005F02E5'], [\$rsidP = '005F02E5']) [*line 210*]

Function Parameters:

- *string* **\$rsidR**
- *string* **\$rsidRDefault**
- *string* **\$rsidP**

Generate w:p

- **Access** protected

void function CreateFootnote::generatePPR() [*line 237*]

Generate w:ppr

- **Access** protected

void function CreateFootnote::generateR() [*line 274*]

Generate w:r

- **Access** protected

void function CreateFootnote::generateSEPARATOR([\$type = 'separator']) [*line 226*]

Function Parameters:

- *string* **\$type**

Generate w:separator

- **Access** protected

void function CreateFootnote::generateSPACING([\$after = '0'], [\$line = '240'], [\$lineRule = 'auto']) [*line 254*]

Function Parameters:

- *string* **\$after**
- *string* **\$line**
- *string* **\$lineRule**

Generate w:spacing

- **Access** protected

CreateFootnote function CreateFootnote::getInstance() [*line 92*]

- **Static**
- **Access** public

void function CreateFootnote::__destruct() [*line 71*]

Destruct

- **Access** public

string function CreateFootnote::__toString() [*line 81*]

- **Access** public

Class CreateGraphic

[*line 29*]

Create graphics (charts)

- **Package** elements
- **Version** 2.2
- **Copyright** Copyright (c) 2009-2011 Narcea Producciones Multimedia S.L. (<http://www.2mdc.com>)
- **Link** <http://www.phpdocx.com>
- **Since** Class available since Release 1.0
- **License** http://www.phpdocx.com/wp-content/themes/lightword/pro_license.php

CreateGraphic::NAMESPACEWORD

= 'c' [*line 31*]

CreateGraphic::\$_xmlChart

<*type*> = [*line 38*]

- **Access** protected

Constructor *void* function CreateGraphic::__construct() [*line 163*]

Construct

- **Access** public

void function CreateGraphic::createCHARTXML(\$args[0]) [*line 315*]

Function Parameters:

- *array* **\$args[0]**

Create chart xml

- **Access** protected

void function CreateGraphic::createDOCUEMNTXML(\$args[0]) [*line 507*]

Function Parameters:

- *array* **\$args[0]**

Create document xml

- **Access** protected

boolean function CreateGraphic::createGraphic(\$args[0], \$args[1]) [*line 292*]

Function Parameters:

- *array* **\$args[0]**
- *array* **\$args[1]**

Create graphic

- **Access** public

void function CreateGraphic::generateAUTO([\$val = '1']) [*line 550*]

Function Parameters:

- *string* \$val

Generate w:auto

- **Access** protected

void function CreateGraphic::generateAUTOTITLEDELETED([\$val = '1']) [*line 566*]

Function Parameters:

- *string* \$val

Generate w:autotitledeleted

- **Access** protected

void function CreateGraphic::generateAXAXID([\$val = '59034624']) [*line 583*]

Function Parameters:

- *<type>* \$val

Generate w:axId

- **Access** protected

void function CreateGraphic::generateAXID([\$val = '59034624']) [*line 599*]

Function Parameters:

- *string* **\$val**

Generate w:axid

- **Access** protected

void function CreateGraphic::generateAXPOS([\$val = 'b']) [*line 615*]

Function Parameters:

- *string* **\$val**

Generate w:axPos

- **Access** protected

void function CreateGraphic::generateBARChart() [*line 629*]

Generate w:barChart

- **Access** protected

void function CreateGraphic::generateBARDIR([\$val = 'bar']) [*line 646*]

Function Parameters:

- *string* \$val

Generate w:barDir

- **Access** protected

void function CreateGraphic::generateBODYPR() [*line 661*]

Generate w:bodypr

- **Access** protected

void function CreateGraphic::generateCAT() [*line 675*]

Generate w:cat

- **Access** protected

void function CreateGraphic::generateCATAX() [*line 690*]

Generate w:catAx

- **Access** protected

void function CreateGraphic::generateCHART() [*line 705*]

Generate w:chart

- **Access** protected

void function CreateGraphic::generateCHARTSPACE() [*line 720*]

Generate chartspace XML

- **Access** protected

void function CreateGraphic::generateCROSSAX([\$val = '59040512']) [*line 738*]

Function Parameters:

- *string* \$val

Generate w:crossAx

- **Access** protected

void function CreateGraphic::generateCROSSBETWEEN([\$val = 'between']) [*line 754*]

Function Parameters:

- *string* \$val

Generate w:crossBetween

- **Access** protected

void function CreateGraphic::generateCROSSES([\$val = 'autoZero']) [*line 771*]

Function Parameters:

- *string* **\$val**

Generate w:crosses

- **Access** protected

void function CreateGraphic::generateDATE1904([\$val = '1']) [*line 788*]

Function Parameters:

- *string* **\$val**

Generate w:date1904

- **Access** protected

void function CreateGraphic::generateDEFRPR() [*line 805*]

Generate w:defrpr

- **Access** protected

void function CreateGraphic::generateDLBLS() [line 820]

Generate w:dLbIs

- **Access** protected

void function CreateGraphic::generateDOCUMENTCHART() [line 836]

Generate w:chart

- **Access** protected

void function CreateGraphic::generateEXTERNALDATA([\$val = 'rld1']) [line 856]

Function Parameters:

- *string* **\$val**

Generate w:externalData

- **Access** protected

void function CreateGraphic::generateF([\$val = 'Hoja1!\$B\$1']) [line 872]

Function Parameters:

- *string* \$val

Generate w:f

- **Access** protected

void function CreateGraphic::generateFIRSTSLICEANG([\$val = '0']) [*line 888*]

Function Parameters:

- *string* \$val

Generate w:firstSliceAng

- **Access** protected

void function CreateGraphic::generateFORMATCODE([\$val = 'General']) [*line 904*]

Function Parameters:

- *string* \$val

Generate w:formatCode

- **Access** protected

void function CreateGraphic::generateGROUPING([\$val = 'stacked']) [*line 921*]

Function Parameters:

- *string* \$val

Generate w:grouping

- **Access** protected

void function CreateGraphic::generateIDX([\$val = '0']) [*line 937*]

Function Parameters:

- *string* \$val

Generate w:idx

- **Access** protected

void function CreateGraphic::generateLANG([\$val = 'es-ES']) [*line 953*]

Function Parameters:

- *string* \$val

Generate w:lang

- **Access** protected

void function CreateGraphic::generateLAYOUT() [*line 970*]

Generate w:layout

- **Access** protected

void function CreateGraphic::generateLBLALGN([\$val = 'ctr']) [*line 986*]

Function Parameters:

- *string* \$val

Generate w:lblAlign

- **Access** protected

void function CreateGraphic::generateLBLOFFSET([\$val = '100']) [*line 1002*]

Function Parameters:

- *string* \$val

Generate w:lblOffset

- **Access** protected

void function CreateGraphic::generateLEGEND() [*line 1016*]

Generate w:legend

- **Access** protected

void function CreateGraphic::generateLEGENDFONT([\$font = "]) [*line 1034*]

Function Parameters:

- *string* **\$font**

Generate c:layout

- **Access** protected

void function CreateGraphic::generateLEGENDPOS([\$val = 'r']) [*line 1052*]

Function Parameters:

- *string* **\$val**

Generate w:legendPos

- **Access** protected

void function CreateGraphic::generateLINECHART() [*line 1067*]

Generate w:lineChart

- **Access** protected

void function CreateGraphic::generateLN() [*line 1083*]

Generate w:ln

- **Access** protected

void function CreateGraphic::generateLSTSTYLE() [*line 1097*]

Generate w:lstyle

- **Access** protected

void function CreateGraphic::generateMAJORGRIDLINES() [*line 1112*]

Generate w:majorGridlines

- **Access** protected

void function CreateGraphic::generateNOFILL() [*line 1126*]

Generate w:noFill

- **Access** protected

void function CreateGraphic::generateNUMCACHE() [*line 1140*]

Generate w:numcache

- **Access** protected

void function CreateGraphic::generateNUMFMT([\$formatCode = 'General'], [\$sourceLinked = '1']) [line 1157]

Function Parameters:

- *string* **\$formatCode**
- *string* **\$sourceLinked**

Generate w:numFmt

- **Access** protected

void function CreateGraphic::generateNUMREF() [line 1175]

Generate w:numRef

- **Access** protected

void function CreateGraphic::generateORDER([\$val = '0']) [line 1191]

Function Parameters:

- *string* **\$val**

Generate w:order

- **Access** protected

void function CreateGraphic::generateORIENTATION([\$val = 'minMax']) [line 1207]

Function Parameters:

- *string* \$val

Generate w:orientation

- **Access** protected

void function CreateGraphic::generateOVERLAP([\$val = '100']) [*line 1222*]

Function Parameters:

- *string* \$val

Generate w:overlap

- **Access** protected

void function CreateGraphic::generatePIECHART() [*line 1237*]

Generate w:piechart

- **Access** protected

void function CreateGraphic::generatePLOTAREA() [*line 1253*]

Generate w:plotarea

- **Access** protected

void function CreateGraphic::generatePLOTVISONLY([\$val = '1']) [line 1269]

Function Parameters:

- *string \$val*

Generate w:polVisOnly

- **Access** protected

void function CreateGraphic::generatePT([\$idx = '0']) [line 1285]

Function Parameters:

- *string \$idx*

Generate w:pt

- **Access** protected

void function CreateGraphic::generatePTCOUNT([\$val = '1']) [line 1301]

Function Parameters:

- *string \$val*

Generate w:ptcount

- **Access** protected

void function CreateGraphic::generateRICH() [*line 1316*]

Generate w:rich

- **Access** protected

void function CreateGraphic::generateSCALING() [*line 1331*]

Generate w:scaling

- **Access** protected

void function CreateGraphic::generateSER() [*line 1346*]

Generate w:ser

- **Access** protected

void function CreateGraphic::generateSHAPE([*\$val = 'box'*]) [*line 1362*]

Function Parameters:

- *string* **\$val**

Generate w:shape

- **Access** protected

void function CreateGraphic::generateSHOWPERCENT([\$val = '0']) [line 1378]

Function Parameters:

- *string \$val*

Generate w:showPercent

- **Access** protected

void function CreateGraphic::generateSPPR() [line 1393]

Generate w:spPr

- **Access** protected

void function CreateGraphic::generateSTRCACHE() [line 1408]

Generate w:strcache

- **Access** protected

void function CreateGraphic::generateSTRREF() [line 1423]

Generate w:strref

- **Access** protected

void function CreateGraphic::generateSTYLE([\$val = '2']) [*line 1439*]

Function Parameters:

- *string* \$val

Generate w:style

- **Access** protected

void function CreateGraphic::generateTICKLBLPOS([\$val = 'nextTo']) [*line 1457*]

Function Parameters:

- *string* \$val

Generate w:tickLbIPos

- **Access** protected

void function CreateGraphic::generateTITLE() [*line 1472*]

Generate w:title

- **Access** protected

void function CreateGraphic::generateTITLELAYOUT([\$nombre = "]) [line 1488]

Function Parameters:

- *string* **\$nombre**

Generate w:titlelayout

- **Access** protected

void function CreateGraphic::generateTITLEP() [line 1503]

Generate w:titlep

- **Access** protected

void function CreateGraphic::generateTITLEPPR() [line 1518]

Generate w:titleppr

- **Access** protected

void function CreateGraphic::generateTITLER() [line 1533]

Generate w:titler

- **Access** protected

void function CreateGraphic::generateTITLERFONTS([\$font = "]) [line 1549]

Function Parameters:

- *string* **\$font**

Generate w:titerfonts

- **Access** protected

void function CreateGraphic::generateTITLERPR([\$lang = 'es-ES']) [*line 1567*]

Function Parameters:

- **\$lang**

Generate w:titerpr

- **Access** protected

void function CreateGraphic::generateTITLET([\$nombre = ""]) [*line 1583*]

Function Parameters:

- *string* **\$nombre**

Generate w:titlet

- **Access** protected

void function CreateGraphic::generateTITLETX() [line 1598]

Generate w:titlex

- **Access** protected

void function CreateGraphic::generateTX() [line 1613]

Generate w:tx

- **Access** protected

void function CreateGraphic::generateV([\$idx = 'Ventas']) [line 1629]

Function Parameters:

- *string* **\$idx**

Generate w:v

- **Access** protected

void function CreateGraphic::generateVAL() [line 1643]

Generate w:val

- **Access** protected

void function CreateGraphic::generateVALAX() [*line 1658*]

Generate w:valAx

- **Access** protected

void function CreateGraphic::generateVARYCOLORS([*\$val = '1'*]) [*line 1675*]

Function Parameters:

- *string* **\$val**

Generate w:varyColors

- **Access** protected

CreateGraphic function CreateGraphic::getInstance() [*line 210*]

- **Static**
- **Access** public

string function CreateGraphic::getName() [*line 257*]

Getter. Name

- **Access** public

string function CreateGraphic::getRId() [*line 235*]

Getter. Rid

- **Access public**

string function CreateGraphic::getXmlChart() [*line 279*]

Getter. Xml chart

- **Access public**

void function CreateGraphic::setName(\$name) [*line 246*]

Function Parameters:

- *string* **\$name**

Setter. Name

- **Access public**

void function CreateGraphic::setRId(\$rId) [*line 224*]

Function Parameters:

- *string* **\$rId**

Setter. Rid

- **Access public**

void function CreateGraphic::setXmlChart(\$xmlChart) [*line 268*]

Function Parameters:

- *string* **\$xmlChart**

Setter. Xml chart

- **Access** public

void function CreateGraphic::__destruct() [*line 189*]

Destruct

- **Access** public

string function CreateGraphic::__toString() [*line 199*]

- **Access** public

Class CreateHeader

[*line 29*]

Create header

- **Package** elements
- **Version** 1.0
- **Copyright** Copyright (c) 2009-2011 Narcea Producciones Multimedia S.L. (<http://www.2mdc.com>)
- **Link** <http://www.phpdocx.com>
- **Since** Class available since Release 1.0
- **License** http://www.phpdocx.com/wp-content/themes/lightword/pro_license.php

Constructor *void* function CreateHeader::__construct() [*line 44*]

Construct

- **Access** public

void function CreateHeader::createHeader(0, 1) [*line 114*]

Function Parameters:

- *string* **0** args[0]
- *array* **1** args[1]

Create header

- **Access** public

void function CreateHeader::generateHDR() [*line 102*]

Generate hdr token

- **Access** protected

void function CreateHeader::generateP() [*line 88*]

Generate w:p

- **Access** protected

CreateHeader function CreateHeader::getInstance() [*line 75*]

- **Static**
- **Access** public

void function CreateHeader::__destruct() [*line 54*]

Destruct

- **Access** public

string function CreateHeader::__toString() [*line 64*]

- **Access** public

Class CreateImage [*line 29*]

Create images

- **Package** elements
- **Version** 1.0
- **Copyright** Copyright (c) 2009-2011 Narcea Producciones Multimedia S.L. (<http://www.2mdc.com>)
- **Link** <http://www.phpdocx.com>
- **Since** Class available since Release 1.0
- **License** http://www.phpdocx.com/wp-content/themes/lightword/pro_license.php

CreteImage::CONSTWORD

= 360000 [*line 34*]

CreteImage::NAMESPACEWORD

= 'wp' [*line 31*]

CreteImage::NAMESPACEWORD1

= 'a' [*line 32*]

CreteImage::NAMESPACEWORD2

= 'pic' [*line 33*]

CreteImage::TAMBORDER

= 12700 [*line 35*]

Constructor *void* function CreteImage::__construct() [*line 127*]

Construct

- **Access** public

void function CreteImage::createImage(\$args[0]) [*line 228*]

Function Parameters:

- *array* **\$args[0]**

Create image

- **Access** public

CreateImage function *CreateImage::getInstance()* [*line 170*]

- **Static**
- **Access** public

<*type*> function *CreateImage::getName()* [*line 195*]

Getter. Name

- **Access** public

<*type*> function *CreateImage::getRid()* [*line 217*]

Getter. Rid

- **Access** public

void function *CreateImage::setName(\$name)* [*line 184*]

Function Parameters:

- *string* **\$name**

Setter. Name

- **Access** public

void function CreateImage::setRId(\$rId) [line 206]

Function Parameters:

- *string* **\$rId**

Setter. Rid

- **Access** public

void function CreateImage::__destruct() [line 149]

Destruct

- **Access** public

string function CreateImage::__toString() [line 159]

- **Access** public

Class CreateLink

[line 29]

Create links using text strings

- **Package** elements
- **Version** 1.0
- **Copyright** Copyright (c) 2009-2011 Narcea Producciones Multimedia S.L. (<http://www.2mdc.com>)
- **Link** <http://www.phpdocx.com>
- **Since** Class available since Release 1.0
- **License** http://www.phpdocx.com/wp-content/themes/lightword/pro_license.php

Constructor *void* function CreateLink::__construct() [*line 62*]

Construct

- **Access** public

void function CreateLink::createLink(\$arrArgs[0], \$arrArgs[1], \$arrArgs[2]) [*line 144*]

Function Parameters:

- *string* **\$arrArgs[0]** Text to add
- *string* **\$arrArgs[1]** URL to add
- *string* **\$arrArgs[2]** R FONTS

Create a link

- **Access** public

void function CreateLink::generateFLDCHAR(\$fldCharType) [*line 173*]

Function Parameters:

- *string* **\$fldCharType**

Generate w:fldChar

- **Access** protected

void function CreateLink::generateHYPERLINK(\$type) [line 188]

Function Parameters:

- *string* **\$type**

Generate w:hyperlink

- **Access** protected

void function CreateLink::generateINSTRTEXT([\$link = 'http://localhost'], \$link.) [line 201]

Function Parameters:

- *string* **\$link**. Optional, use http://localhost as default
- **\$link**

Generate w:instrText

- **Access** protected

void function CreateLink::generatePROOFERR(\$type) [line 216]

Function Parameters:

- *string* **\$type**

Generate w:proofErr

- **Access** protected

void function CreateLink::generateR() [*line 230*]

Generate w:r

- **Access** protected

void function CreateLink::generateRSTYLE(\$val) [*line 255*]

Function Parameters:

- *string* \$val

Generate w:rStyle

- **Access** protected

string function CreateLink::getFont() [*line 131*]

Getter. Access to font var

- **Access** public

CreateLink function CreateLink::getInstance() [*line 95*]

Singleton, return instance of class

- **Static**
- **Access** public

string function CreateLink::getLink() [*line 109*]

Getter. Access to link var

- **Access** public

string function CreateLink::getTitle() [*line 120*]

Getter. Access to title var

- **Access** public

void function CreateLink::__destruct() [*line 72*]

Destruct

- **Access** public

string function CreateLink::__toString() [*line 83*]

Magic method, returns current XML

- **Access** public

Class CreateList

[line 29]

Create lists

- **Package** elements
- **Version** 1.0
- **Copyright** Copyright (c) 2009-2011 Narcea Producciones Multimedia S.L.
(<http://www.2mdc.com>)
- **Link** <http://www.phpdocx.com>
- **Since** Class available since Release 1.0
- **License** http://www.phpdocx.com/wp-content/themes/lightword/pro_license.php

CreateList::\$data

array = [line 54]

- **Access** public

CreateList::\$font

string = [line 48]

- **Access** public

CreateList::\$list

mixed = [line 36]

- **Access** public

CreateList::\$val

array = [line 42]

- **Access** public

Constructor *void* function CreateList::__construct() *[line 74]*

Construct

- **Access** public

void function CreateList::addList(\$list) *[line 148]*

Function Parameters:

- *string* **\$list**

Add list

- **Access** protected

void function CreateList::createList(0, 1) *[line 121]*

Function Parameters:

- *array* **0** args[0]
- *array* **1** args[1]

Create list

- **Access** public

void function CreateList::generateLLFO([\$val = 0]) [*line 159*]

Function Parameters:

- *int* **\$val**

Generate w:ilfo

- **Access** protected

void function CreateList::generateLLVL([\$val = ""]) [*line 175*]

Function Parameters:

- *string* **\$val**

Generate w:ilvl

- **Access** protected

void function CreateList::generateLISTPR() [*line 189*]

Generate w:listpr

- **Access** protected

void function CreateList::generateNUMID(\$val) [*line 203*]

Function Parameters:

- *int* \$val

Generate w:numid

- **Access** protected

void function CreateList::generateNUMPR() [*line 217*]

Generate w:numpr

- **Access** protected

void function CreateList::generatePSTYLE(\$val) [*line 231*]

Function Parameters:

- *string* \$val

Generate w:pstyle

- **Access** protected

CreateList function *CreateList::getInstance()* [*line 106*]

- **Static**
- **Access** public

void function *CreateList::runArray(\$dat, \$val, \$depth, [\$font = "])* [*line 249*]

Function Parameters:

- *array* **\$dat**
- *string* **\$val**
- *int* **\$depth**
- *string* **\$font**

Recursive generation of lists

- **Access** protected

void function *CreateList::__destruct()* [*line 84*]

Destruct

- **Access** public

string function *CreateList::__toString()* [*line 94*]

- **Access** public

Class CreatePage

[line 29]

Create pages

- **Package** elements
- **Version** 1.0
- **Copyright** Copyright (c) 2009-2011 Narcea Producciones Multimedia S.L. (http://www.2mdc.com)
- **Link** <http://www.phpdocx.com>
- **Since** Class available since Release 1.0
- **License** http://www.phpdocx.com/wp-content/themes/lightword/pro_license.php

CreatePage::\$_xml

string = [line 36]

- **Access** protected

Constructor *void* function CreatePage::__construct() [line 50]

Construct

- **Access** public

void function CreatePage::createPage() [line 92]

Create page

- **Access** public

void function CreatePage::createSECTPR(0) [*line 120*]

Function Parameters:

- array 0 args[0]

Create sectpr

- Access public

void function CreatePage::generateBR([\$type = ""]) [*line 261*]

Function Parameters:

- string \$type

Generate w:br

- Access protected

void function CreatePage::generateCOL([\$w = "], [\$space = '708']) [*line 236*]

Function Parameters:

- string \$w
- string \$space

Generate w:col

- **Deprecated**
- **Access** protected

void function CreatePage::generateCOLS([\$num = "], [\$sep = "], [\$space = '708'], [\$equalWidth = "]) [*line 219*]

Function Parameters:

- *string* **\$num**
- *string* **\$sep**
- *string* **\$space**
- *string* **\$equalWidth**

Generate w:cols

- **Access** protected

void function CreatePage::generateDOCGRID([\$linepitch = '360']) [*line 247*]

Function Parameters:

- *string* **\$linepitch**

Generate w:docgrid

- **Access** protected

void function CreatePage::generatePageBreak(\$type) [*line 103*]

Function Parameters:

- *string* **\$type**

Generate pagebreak

- **Access** public

void function CreatePage::generatePGMAR(\$args[0]) [line 183]

Function Parameters:

- *array* **\$args[0]**

Generate w:pgmar

- **Access** protected

void function CreatePage::generatePGSZ([\$w = '11906'], [\$h = '16838'], [\$orient = ""]) [line 161]

Function Parameters:

- *string* **\$w**
- *string* **\$h**
- *string* **\$orient**

Generate w:pgsz

- **Access** protected

void function CreatePage::generateSECTIONSECTPR([\$rId = '12240']) [line 275]

Function Parameters:

- *string* \$rId

Generate w:sectionsectpr

- **Access** protected

void function CreatePage::generateSECTPR([\$rId = '12240']) [*line 142*]

Function Parameters:

- *string* \$rId

Generate w:sectpr

- **Access** protected

void function CreatePage::generateTITLEPG() [*line 292*]

Generate w:titlepg

- **Access** protected

CreatePage function CreatePage::getInstance() [*line 81*]

- **Static**
- **Access** public

void function CreatePage::__destruct() [*line 60*]

Destruct

- **Access** public

string function CreatePage::__toString() [*line 70*]

- **Access** public

Class CreateSettings

[*line 29*]

Create default settings

- **Package** elements
- **Version** 1.0
- **Copyright** Copyright (c) 2009-2011 Narcea Producciones Multimedia S.L. (<http://www.2mdc.com>)
- **Link** <http://www.phpdocx.com>
- **Since** Class available since Release 1.0
- **License** http://www.phpdocx.com/wp-content/themes/lightword/pro_license.php

CreateSettings::\$_xml

mixed = [*line 36*]

- **Access** protected

Constructor *void* function CreateSettings::__construct() [*line 49*]

Construct

- **Access** public

void function CreateSettings::generateSettings() [*line 92*]

Generate settings

- **Access** public

CreateLink function CreateSettings::getInstance() [*line 81*]

Singleton, return instance of class

- **Static**
- **Access** public

void function CreateSettings::__destruct() [*line 59*]

Destruct

- **Access** public

string function CreateSettings::__toString() [*line 70*]

Magic method, returns current XML

- **Access** public

Class CreateStyle

[line 31]

Create styles

- **Package** elements
- **Version** 2.1
- **Copyright** Copyright (c) 2009-2011 Narcea Producciones Multimedia S.L.
(<http://www.2mdc.com>)
- **Link** <http://www.phpdocx.com>
- **Since** Class available since Release 1.0
- **License** http://www.phpdocx.com/wp-content/themes/lightword/pro_license.php

CreateStyle::\$_xml

string = [line 38]

- **Access** protected

Constructor *void* function CreateStyle::__construct() *[line 51]*

Construct

- **Access** public

void function CreateStyle::addStyle(\$args[0]) *[line 96]*

Function Parameters:

- *array* **\$args[0]**

Add style

- **Access public**

void function CreateStyle::addStyleTabla(\$param) [*line 1525*]

Function Parameters:

- *array* **\$param**

Add table style

- **Access public**

void function CreateStyle::createStyle([\$lang = 'en-US']) [*line 452*]

Function Parameters:

- *string* **\$lang**

Create style

- **Access public**

void function CreateStyle::generateAUTOREDEFINE() [line 1654]

Generate w:auto redefine

- **Access** protected

void function CreateStyle::generateB() [line 2494]

Generate w:b

- **Access** protected

void function CreateStyle::generateBASEDON(\$val) [line 1582]

Function Parameters:

- *string* **\$val**

Generate w:basedon

- **Access** protected

void function CreateStyle::generateBCS() [line 2507]

Generate w:bcs

- **Access** protected

void function CreateStyle::generateBOTTOM(\$w, \$type) [line 2406]

Function Parameters:

- *string* **\$w**
- *string* **\$type**

Generate w:bottom

- **Access** protected

void function CreateStyle::generateCOLOR(\$val, [\$themeColor = "], [\$themeShade = "]) [*line 2579*]

Function Parameters:

- *string* **\$val**
- *string* **\$themeColor**
- *string* **\$themeShade**

Generate w:color

- **Access** protected

void function CreateStyle::generateCONTEXTUALSPACING() [*line 1920*]

Generate w:contextualspacing

- **Access** protected

void function CreateStyle::generatel([\$val = "]) [*line 2521*]

Function Parameters:

- *string* \$val

Generate w:i

- **Access** protected

void function CreateStyle::generateICS([\$val = ""]) [*line 2540*]

Function Parameters:

- *string* \$val

Generate w:ics

- **Access** protected

void function CreateStyle::generateLVL(\$val) [*line 1793*]

Function Parameters:

- *string* \$val

Generate w:ilvl

- **Access** protected

void function CreateStyle::generateIND(\$left) [*line 1949*]

Function Parameters:

- *string* **\$left**

Generate w:ind

- **Access** protected

void function CreateStyle::generateKEEPLINES() [*line 1807*]

Generate w:keplines

- **Access** protected

void function CreateStyle::generateKEEPNEXT() [*line 1721*]

Generate w:keepnext

- **Access** protected

void function CreateStyle::generateKERN(\$val) [*line 1906*]

Function Parameters:

- *string* **\$val**

Generate w:kern

- **Access** protected

void function CreateStyle::generateLEFT(\$w, \$type) [*line 2389*]

Function Parameters:

- *string* **\$w**
- *string* **\$type**

Generate w:left

- **Access** protected

void function CreateStyle::generateLINK(\$val) [*line 1612*]

Function Parameters:

- *string* **\$val**

Generate w:link

- **Access** protected

void function CreateStyle::generateNAME(\$val) [*line 1568*]

Function Parameters:

- *string* **\$val**

Generate w:name

- **Access** protected

void function CreateStyle::generateNEXT(\$val) [*line 1597*]

Function Parameters:

- *string* \$val

Generate w:next

- **Access** protected

void function CreateStyle::generateNUMPR() [*line 1779*]

Generate w:numpr

- **Access** protected

void function CreateStyle::generateOUTLINEVL(\$val) [*line 1934*]

Function Parameters:

- *string* \$val

Generate w:outlinevl

- **Access** protected

void function CreateStyle::generatePBDR() [line 1820]

Generate w:pbdr

- **Access** protected

void function CreateStyle::generatePBDR_BOTTOM(\$val, \$sz, \$space, \$color, \$themeColor) [line 1837]

Function Parameters:

- *string* **\$val**
- *string* **\$sz**
- *string* **\$space**
- *string* **\$color**
- *string* **\$themeColor**

Generate w:pbdr

- **Access** protected

void function CreateStyle::generatePPR() [line 1708]

Generate w:ppr

- **Access** protected

void function CreateStyle::generateQFORMAT() [line 1667]

Generate w:qformat

- **Access** protected

void function CreateStyle::generateRFONTS(\$asciiTheme, \$eastAsiaTheme, \$hAnsiTheme, \$cstheme) [line 2453]

Function Parameters:

- *string* **\$asciiTheme**
- *string* **\$eastAsiaTheme**
- *string* **\$hAnsiTheme**
- *string* **\$cstheme**

Generate w:rfonts

- **Access** protected

void function CreateStyle::generateRFONTS2(\$ascii, \$hAnsi, \$cs) [line 2478]

Function Parameters:

- *string* **\$ascii**
- *string* **\$hAnsi**
- *string* **\$cs**

Generate w:rfonts

- **Access** protected

void function CreateStyle::generateRIGHT(\$w, \$type) [line 2423]

Function Parameters:

- *string* **\$w**
- *string* **\$type**

Generate w:right

- **Access** protected

void function CreateStyle::generateRPR() [*line 2436*]

Generate w:rpr

- **Access** protected

void function CreateStyle::generateRPR_SPACING(\$val) [*line 1891*]

Function Parameters:

- *string* \$val

Generate w:spacing

- **Access** protected

void function CreateStyle::generateRSID(\$val) [*line 1681*]

Function Parameters:

- *string* \$val

Generate w:rsid

- **Access** protected

void function CreateStyle::generateSEMIHIDDEN() [*line 1695*]

Generate w:semihidden

- **Access** protected

void function CreateStyle::generateSHD(\$val, [\$color = ""], [\$fill = ""], [\$themeFill = ""], [\$themeFillTint = ""]) [*line 1981*]

Function Parameters:

- *string* **\$val**
- *string* **\$color**
- *string* **\$fill**
- *string* **\$themeFill**
- *string* **\$themeFillTint**

Generate w:shd

- **Access** protected

void function CreateStyle::generateSPACING(\$before, \$after, \$line, \$lineRule) [*line 1859*]

Function Parameters:

- *string* **\$before**
- *string* **\$after**
- *string* **\$line**
- *string* **\$lineRule**

Generate w:spacing

- **Access** protected

void function CreateStyle::generateSTYLE(\$type, \$styleId, [\$default = ''], [\$customStyle = '']) [line 1544]

Function Parameters:

- *string* **\$type**
- *string* **\$styleId**
- *string* **\$default**
- *string* **\$customStyle**

Generate w:style

- **Access** protected

void function CreateStyle::generateSZ(\$val) [line 2604]

Function Parameters:

- *string* **\$val**

Generate w:sz

- **Access** protected

void function CreateStyle::generateSZCS(\$val) [line 2619]

Function Parameters:

- *string* **\$val**

Generate w:szcs

- **Access** protected

void function CreateStyle::generateTABCENTER(\$pos) [*line 1748*]

Function Parameters:

- *string* **\$pos**

Generate w:tabcenter

- **Access** protected

void function CreateStyle::generateTABRIGHT(\$pos) [*line 1764*]

Function Parameters:

- *string* **\$pos**

Generate w:tabright

- **Access** protected

void function CreateStyle::generateTABS() [*line 1734*]

Generate w:tabs

- **Access** protected

void function CreateStyle::generateTBLBORDERS() [line 2069]

Generate w:tblborders

- **Access** protected

void function CreateStyle::generateTBLBORDERS_BOTTOM(\$val, [\$sz = "], [\$space = "], [\$color = "], [\$themeColor = "], [\$themeTint = "]) [line 2180]

Function Parameters:

- *string* **\$val**
- *string* **\$sz**
- *string* **\$space**
- *string* **\$color**
- *string* **\$themeColor**
- *string* **\$themeTint**

Generate w:bottom

- **Access** protected

void function CreateStyle::generateTBLBORDERS_INSIDEH(\$val, [\$sz = "], [\$space = "], [\$color = "], [\$themeColor = "], [\$themeTint = "]) [line 2272]

Function Parameters:

- *string* **\$val**
- *string* **\$sz**
- *string* **\$space**
- *string* **\$color**
- *string* **\$themeColor**

- *string* **\$themeTint**

Generate w:insideh

- **Access** protected

void function CreateStyle::generateTBLBORDERS_INSIDEV(\$val, [\$sz = ""], [\$space = ""], [\$color = ""], [\$themeColor = ""], [\$themeTint = ""]) [*line 2317*]

Function Parameters:

- *string* **\$val**
- *string* **\$sz**
- *string* **\$space**
- *string* **\$color**
- *string* **\$themeColor**
- *string* **\$themeTint**

Generate w:insidev

- **Access** protected

void function CreateStyle::generateTBLBORDERS_LEFT(\$val, [\$sz = ""], [\$space = ""], [\$color = ""], [\$themeColor = ""], [\$themeTint = ""]) [*line 2134*]

Function Parameters:

- *string* **\$val**
- *string* **\$sz**
- *string* **\$space**
- *string* **\$color**
- *string* **\$themeColor**
- *string* **\$themeTint**

Generate w:left

- **Access** protected

void function CreateStyle::generateTBLBORDERS_RIGHT(\$val, [\$sz = "], [\$space = "], [\$color = "], [\$themeColor = "], [\$themeTint = "]) [*line 2228*]

Function Parameters:

- *string* **\$val**
- *string* **\$sz**
- *string* **\$space**
- *string* **\$color**
- *string* **\$themeColor**
- *string* **\$themeTint**

Generate w:right

- **Access** protected

void function CreateStyle::generateTBLBORDERS_TOP(\$val, [\$sz = "], [\$space = "], [\$color = "], [\$themeColor = "], [\$themeTint = "]) [*line 2088*]

Function Parameters:

- *string* **\$val**
- *string* **\$sz**
- *string* **\$space**
- *string* **\$color**
- *string* **\$themeColor**
- *string* **\$themeTint**

Generate w:top

- **Access** protected

void function CreateStyle::generateTBLCELLMAR() [line 2356]

Generate w:tblcellmar

- **Access** protected

void function CreateStyle::generateTBLIND(\$w, \$type) [line 2028]

Function Parameters:

- *string* **\$w**
- *string* **\$type**

Generate w:tblind

- **Access** protected

void function CreateStyle::generateTBLPR() [line 2014]

Generate w:tblpr

- **Access** protected

void function CreateStyle::generateTBLSTYLECOLBANDSIZE(\$val) [line 2057]

Function Parameters:

- *string* **\$val**

Generate w:tblstylecolbandsize

- **Access** protected

void function CreateStyle::generateTBLSTYLROWBANDSIZE(\$val) [*line 2043*]

Function Parameters:

- *string* **\$val**

Generate w:tblstylerowbandsize

- **Access** protected

void function CreateStyle::generateTCPR() [*line 1963*]

Generate w:tcpr

- **Access** protected

void function CreateStyle::generateTOP(\$w, \$type) [*line 2372*]

Function Parameters:

- *string* **\$w**
- *string* **\$type**

Generate w:top

- **Access** protected

void function CreateStyle::generateU([\$val = "]) [*line 2559*]

Function Parameters:

- *string* \$val

Generate w:u

- **Access** protected

void function CreateStyle::generateUIPRIORITY(\$val) [*line 1627*]

Function Parameters:

- *string* \$val

Generate w:uipriority

- **Access** protected

void function CreateStyle::generateUNHIDEWHENUSED() [*line 1641*]

Generate w:unhidwhenused

- **Access** protected

void function CreateStyle::generateVERTALIGN([\$val = 'superscript']) [*line 2634*]

Function Parameters:

- *string* \$val

Generate w:vertAlign

- **Access** protected

CreateStyle function CreateStyle::getInstance() [*line 82*]

- **Static**
- **Access** public

void function CreateStyle::__destruct() [*line 61*]

Destruct

- **Access** public

string function CreateStyle::__toString() [*line 71*]

- **Access** public

Class CreateStyleTable

[line 29]

Create style table

- **Package** elements
- **Version** 1.0
- **Copyright** Copyright (c) 2009-2011 Narcea Producciones Multimedia S.L. (<http://www.2mdc.com>)
- **Link** <http://www.phpdocx.com>
- **Since** Class available since Release 1.0
- **License** http://www.phpdocx.com/wp-content/themes/lightword/pro_license.php

CreateStyleTable::\$_xml

string = [line 36]

- **Access** protected

Constructor *void* function CreateStyleTable::__construct() [line 49]

Construct

- **Access** public

void function CreateStyleTable::addStyleTable(\$args[0]) [line 94]

Function Parameters:

- *array* **\$args[0]**

Add table style

- **Access** public

void function CreateStyleTable::generateSHD(\$val, [\$color = "], [\$fill = "], [\$themeFill = "], [\$themeFillTint = "]) [*line 518*]

Function Parameters:

- *string* **\$val**
- *string* **\$color**
- *string* **\$fill**
- *string* **\$themeFill**
- *string* **\$themeFillTint**

Generate w:shd

- **Access** protected

void function CreateStyleTable::generateTBLPR() [*line 465*]

Generate w:tblPr

- **Access** protected

void function CreateStyleTable::generateTBLSTYLEPR(\$type) [*line 452*]

Function Parameters:

- *string* **\$type**

Generate w:tblStylePr

- **Access** protected

void function CreateStyleTable::generateTCBORDERS() [*line 497*]

Generate w:tcBorders

- **Access** protected

void function CreateStyleTable::generateTCPR() [*line 481*]

Generate w:tcPr

- **Access** protected

CreateStyleTable function CreateStyleTable::getInstance() [*line 80*]

- **Static**
- **Access** public

void function CreateStyleTable::__destruct() [*line 59*]

Destruct

- **Access** public

string function CreateStyleTable::__toString() [*line 69*]

- **Access public**

Class CreateTable

[line 29]

Create tables

- **Package** elements
- **Version** 1.0
- **Copyright** Copyright (c) 2009-2011 Narcea Producciones Multimedia S.L. (<http://www.2mdc.com>)
- **Link** <http://www.phpdocx.com>
- **Since** Class available since Release 1.0
- **License** http://www.phpdocx.com/wp-content/themes/lightword/pro_license.php

Constructor *void* function CreateTable::__construct() *[line 44]*

Construct

- **Access public**

void function CreateTable::addList(\$list) *[line 137]*

Function Parameters:

- *string* **\$list**

Add list

- **Access** protected

void function CreateTable::createTable(0) [*line 90*]

Function Parameters:

- *array* **0** args[0]

Create table

- **Access** public

void function CreateTable::generateGRIDCOLS(\$w) [*line 148*]

Function Parameters:

- *string* **\$w**

Generate w:gridcols

- **Access** protected

void function CreateTable::generateHMERGE([\$val = ""]) [*line 163*]

Function Parameters:

- *string* **\$val**

Generate w:hmerge

- **Deprecated**
- **Access** protected

void function CreateTable::generateJC([\$val = "]) [*line 174*]

Function Parameters:

- *string* **\$val**

Generate w:jc

- **Access** protected

void function CreateTable::generateP() [*line 187*]

Generate w:p

- **Access** protected

void function CreateTable::generateSHD([\$val = 'horz-cross'], [\$color = 'ff0000'], [\$fill = "], [\$bgcolor = "], [\$themeFill = "]) [*line 204*]

Function Parameters:

- *string* **\$val**
- *string* **\$color**
- *string* **\$fill**
- *string* **\$bgcolor**
- *string* **\$themeFill**

Generate w:shd

- **Access** protected

void function CreateTable::generateTBL() [*line 257*]

Generate w:tbl

- **Access** protected

void function CreateTable::generateTBLBORDERS() [*line 222*]

Generate w:tblborders

- **Access** protected

void function CreateTable::generateTBLBOTTOM([\$val = "single"], [\$sz = "4"], [\$space = '0'], [\$color = 'auto']) [*line 239*]

Function Parameters:

- *string* **\$val**
- *string* **\$sz**
- *string* **\$space**
- *string* **\$color**

Generate w:tblbottom

- **Access** protected

void function CreateTable::generateTBLCELLSPACING([\$w = "], [\$type = "]) [line 286]

Function Parameters:

- *string \$w*
- *string \$type*

Generate w:tblcellspacing

- **Access protected**

void function CreateTable::generateTBLGRID() [line 303]

Generate w:tblgrid

- **Access protected**

void function CreateTable::generateTBLINSIDEH([\$val = "single"], [\$sz = "4"], [\$space = '0'], [\$color = 'auto']) [line 321]

Function Parameters:

- *string \$val*
- *string \$sz*
- *string \$space*
- *string \$color*

Generate w:tblinsideh

- **Access protected**

void function CreateTable::generateTBLINSIDEV([\$val = "single"], [\$sz = "4"], [\$space = '0'], [\$color = 'auto']) [line 343]

Function Parameters:

- *string \$val*
- *string \$sz*
- *string \$space*
- *string \$color*

Generate w:tblinsidev

- **Access protected**

void function CreateTable::generateTBLLEFT([\$val = "single"], [\$sz = "4"], [\$space = '0'], [\$color = 'auto']) [line 364]

Function Parameters:

- *string \$val*
- *string \$sz*
- *string \$space*
- *string \$color*

Generate w:tblleft

- **Access protected**

void function CreateTable::generateTBLLOOK([\$val = '000001E0']) [line 382]

Function Parameters:

- *string \$val*

Generate w:tbllook

- **Access** protected

void function CreateTable::generateTBLOVERLAP([\$val = 'never']) [*line 396*]

Function Parameters:

- *string* **\$val**

Generate w:tbloverlap

- **Access** protected

void function CreateTable::generateTBLPR() [*line 409*]

Generate w:tblpr

- **Access** protected

void function CreateTable::generateTBLRIGHT([\$val = 'single'], [\$sz = '4'], [\$space = '0'], [\$color = 'auto']) [*line 429*]

Function Parameters:

- *string* **\$val**
- *string* **\$sz**
- *string* **\$space**
- *string* **\$color**

Generate w:tblright

- **Access** protected

void function CreateTable::generateTBLSTYLE([\$strVal = 'Tablaconcuadrucula']) [*line 270*]

Function Parameters:

- *string* **\$strVal**

Generate w:tblstyle

- **Access** protected

void function CreateTable::generateTBLTOP([\$val = 'single'], [\$sz = '4'], [\$space = '0'], [\$color = 'auto']) [*line 450*]

Function Parameters:

- *string* **\$val**
- *string* **\$sz**
- *string* **\$space**
- *string* **\$color**

Generate w:tbltop

- **Access** protected

void function CreateTable::generateTBLW([\$type = 'auto'], [\$w = '0']) [*line 469*]

Function Parameters:

- *string* **\$type**
- *string* **\$w**

Generate w:tblw

- **Access** protected

void function CreateTable::generateTC() [*line 483*]

Generate w:tc

- **Access** protected

void function CreateTable::generateTCPR() [*line 495*]

Generate w:tcpr

- **Access** protected

void function CreateTable::generateTCW([\$w = "], [\$type = 'dxa']) [*line 510*]

Function Parameters:

- *string* **\$w**
- *string* **\$type**

Generate w:tcw

- **Access** protected

void function CreateTable::generateTR() [line 524]

Generate w:tr

- **Access** protected

void function CreateTable::generateTRPR() [line 537]

Generate w:trpr

- **Access** protected

void function CreateTable::generateVMERGE([\$val = ""]) [line 552]

Function Parameters:

- *<type>* **\$val**

Generate w:vmerge

- **Deprecated**
- **Access** protected

CreateTable function CreateTable::getInstance() [line 76]

- **Static**
- **Access** public

void function CreateTable::__destruct() [line 54]

Destruct

- **Access** public

string function CreateTable::__toString() [*line 64*]

- **Access** public

Class CreateTableContents

[*line 29*]

Create table of contents

- **Package** elements
- **Version** 1.0
- **Copyright** Copyright (c) 2009-2011 Narcea Producciones Multimedia S.L. (<http://www.2mdc.com>)
- **Link** <http://www.phpdocx.com>
- **Since** Class available since Release 1.0
- **License** http://www.phpdocx.com/wp-content/themes/lightword/pro_license.php

CreateTableContents::\$_xml

string = [*line 36*]

- **Access** protected

Constructor *void* function CreateTableContents::__construct() [*line 51*]

Construct

- **Access** public

void function CreateTableContents::createTableContents(\$font) [*line 97*]

Function Parameters:

- *string* **\$font**

Create table of contents

- **Access** public

void function CreateTableContents::generateFLDSIMPLE([\$instr = 'TOC \"1-4"
 \h \z \u'], \$instr.) [*line 118*]

Function Parameters:

- *string* **\$instr**. Optional, 'TOC \"1-4" \h \z \u' as default
- **\$instr**

Generate w:fldsimple

- **Access** protected

CreateTableContents function CreateTableContents::getInstance() [*line 83*]

- **Static**
- **Access** public

void function CreateTableContents::__destruct() [*line 61*]

Destruct

- **Access** public

string function CreateTableContents::__toString() [*line 72*]

Magic method, returns current XML

- **Access** public

Class CreateText

[*line 29*]

Create text

- **Package** elements
- **Version** 1.0
- **Copyright** Copyright (c) 2009-2011 Narcea Producciones Multimedia S.L. (<http://www.2mdc.com>)
- **Link** <http://www.phpdocx.com>
- **Since** Class available since Release 1.0
- **License** http://www.phpdocx.com/wp-content/themes/lightword/pro_license.php

CreateText::IDTITLE

= 229998237 *[line 31]*

Constructor *void* function CreateText::__construct() *[line 50]*

Destruct

- **Access public**

void function CreateText::createText(\$args[0], \$args[1]) *[line 98]*

Function Parameters:

- *mixed* **\$args[0]**
- *array* **\$args[1]**

Create text

- **Access public**

void function CreateText::createTitle(\$arrArgs[0], \$arrArgs[1]) *[line 162]*

Function Parameters:

- *string* **\$arrArgs[0]**
- *array* **\$arrArgs[1]**

Create title

- **Access public**

void function CreateText::generateB([\$strVal = 'single'], \$val) *[line 224]*

Function Parameters:

- *string* \$val
- \$strVal

Generate w:b

- **Access** protected

void function CreateText::generateBOOKMARKEND(\$id) [*line 395*]

Function Parameters:

- *int* \$id

Generate w:bookmarkend

- **Access** protected

void function CreateText::generateBOOKMARKSTART(\$id, \$name) [*line 378*]

Function Parameters:

- *int* \$id
- *string* \$name

Generate w:bookmarkstart

- **Access** protected

void function CreateText::generateCOLOR([\$val = '000000']) [*line 238*]

Function Parameters:

- *string* \$val

Generate w:color

- **Access** protected

void function CreateText::generateI([\$val = 'single']) [*line 268*]

Function Parameters:

- *string* \$val

Generate w:i

- **Access** protected

void function CreateText::generateJC([\$val = ""]) [*line 253*]

Function Parameters:

- *string* \$val

Generate w:jc

- **Access** protected

void function CreateText::generatePAGEBREAKBEFORE([\$val = 'on']) [*line 330*]

Function Parameters:

- *string* \$val

Generate w:pagebreakbefore

- **Access** protected

void function CreateText::generatePSTYLE([\$val = 'Ttulo']) [*line 314*]

Function Parameters:

- *string* \$val

Generate w:pstyle

- **Access** protected

void function CreateText::generateSZ([\$val = '11']) [*line 283*]

Function Parameters:

- *string* \$val

Generate w:sz

- **Access** protected

void function CreateText::generateU([\$val = 'single']) [line 299]

Function Parameters:

- *string* **\$val**

Generate w:u

- **Access** protected

void function CreateText::generateWIDOWCONTROL([\$val = 'on']) [line 346]

Function Parameters:

- *string* **\$val**

Generate w:widowcontrol

- **Access** protected

void function CreateText::generateWORDWRAP([\$val = 'on']) [line 362]

Function Parameters:

- *string* **\$val**

Generate w:wordwrap

- **Access** protected

CreateText function `CreateText::getInstance()` [*line 83*]

Singleton, return instance of class

- **Static**
- **Access** public

void function `CreateText::__destruct()` [*line 60*]

Destruct

- **Access** public

string function `CreateText::__toString()` [*line 71*]

Magic method, returns current XML

- **Access** public

Class `CreateTheme1` [*line 29*]

- **Package** elements
- **Version** 1.0
- **Copyright** Copyright (c) 2009-2011 Narcea Producciones Multimedia S.L. (http://www.2mdc.com)
- **Link** <http://www.phpdocx.com>
- **Since** Class available since Release 1.0
- **License** http://www.phpdocx.com/wp-content/themes/lightword/pro_license.php

CreateTheme1::NAMESPACEWORD

= 'a' [*line 31*]

CreateTheme1::\$_xml

string = [*line 45*]

- **Access** protected

Constructor *void* function CreateTheme1::__construct() [*line 52*]

Construct

- **Access** public

void function CreateTheme1::createTheme(\$font) [*line 97*]

Function Parameters:

- *string* **\$font**

Create theme

- **Access** public

void function CreateTheme1::generateACCENT1() [line 440]

Generate a:accent1

- **Access** protected

void function CreateTheme1::generateACCENT2() [line 453]

Generate a:accent2

- **Access** protected

void function CreateTheme1::generateACCENT3() [line 466]

Generate a:accent3

- **Access** protected

void function CreateTheme1::generateACCENT4() [line 479]

Generate a:accent4

- **Access** protected

void function CreateTheme1::generateACCENT5() [line 492]

Generate a:accent5

- **Access** protected

void function CreateTheme1::generateACCENT6() [*line 505*]

Generate a:accent6

- **Access** protected

void function CreateTheme1::generateALPHA(\$val) [*line 1061*]

Function Parameters:

- *string* **\$val**

Generate a:alpha

- **Access** protected

void function CreateTheme1::generateBEVELT(\$w, \$h) [*line 1161*]

Function Parameters:

- *string* **\$w**
- *string* **\$h**

Generate a:bevelt

- **Access** protected

void function CreateTheme1::generateBGFILLSTYLELST() [line 1174]

Generate a:bgfillstylelst

- **Access** protected

void function CreateTheme1::generateCAMERA(\$prst) [line 1100]

Function Parameters:

- *string* **\$prst**

Generate a:camera

- **Access** protected

void function CreateTheme1::generateCLRScheme([\$name = 'Office']) [line 340]

Function Parameters:

- *string* **\$name**

Generate a:clrscheme

- **Access** protected

void function CreateTheme1::generateCS([\$typeface = ""]) [line 609]

Function Parameters:

- *string* **\$typeface**

Generate a:cs

- **Access** protected

void function CreateTheme1::generateDK1() [*line 359*]

Generate a:dk1

- **Access** protected

void function CreateTheme1::generateDK2() [*line 401*]

Generate a:dk2

- **Access** protected

void function CreateTheme1::generateEA([\$typeface = '']) [*line 594*]

Function Parameters:

- *string* **\$typeface**

Generate a:ea

- **Access** protected

void function CreateTheme1::generateEFFECTLST() [*line 1014*]

Generate a:effectlst

- **Access** protected

void function CreateTheme1::generateEFFECTLST2() [*line 1074*]

Generate a:effectlst2

- **Access** protected

void function CreateTheme1::generateEFFECTSTYLE() [*line 981*]

Generate a:effectstyle

- **Access** protected

void function CreateTheme1::generateEFFECTSTYLE2() [*line 999*]

Generate a:effectstyle2

- **Access** protected

void function CreateTheme1::generateEFFECTSTYLELST() [*line 967*]

Generate a:effectstylest

- **Access** protected

void function CreateTheme1::generateEXTRACLRSCHEMELST() [*line 1257*]

Generate a:extraclrschemelst

- **Access** protected

void function CreateTheme1::generateFILLSTYLELST() [*line 705*]

Generate a:fillstylelst

- **Access** protected

void function CreateTheme1::generateFILLTORECT(\$l, \$t, \$r, \$b) [*line 1225*]

Function Parameters:

- *string* **\$l**
- *string* **\$t**
- *string* **\$r**
- *string* **\$b**

Generate a:filltorect

- **Access** protected

void function CreateTheme1::generateFMTSCHEME(\$name) [*line 690*]

Function Parameters:

- *string* **\$name**

Generate a:fmtscheme

- **Access** protected

void function CreateTheme1::generateFOLHLINK() [*line 531*]

Generate a:folhlink

- **Access** protected

void function CreateTheme1::generateFONT([\$script = "], [\$typeface = "]) [*line 626*]

Function Parameters:

- *string* **\$script**
- *string* **\$typeface**

Generate a:font

- **Access** protected

void function CreateTheme1::generateFONT2([\$script = "], [\$typeface = "]) [*line 643*]

Function Parameters:

- *string* **\$typeface**
- *string* **\$script** script

Generate a:font

- **Access** protected

void function CreateTheme1::generateFONT3([\$script = "], [\$typeface = "]) [*line 661*]

Function Parameters:

- *string* **\$script**
- *string* **\$typeface**

Generate a:font

- **Access** protected

void function CreateTheme1::generateFONTSHEMA([\$name = 'Office']) [*line 545*]

Function Parameters:

- *string* **\$name**

Generate a:fontschema

- **Access** protected

void function CreateTheme1::generateGRADFILL(\$rotWithShape) [*line 751*]

Function Parameters:

- *string* **\$rotWithShape**

Generate a:gradfill

- **Access** protected

void function CreateTheme1::generateGRADFILL2(\$rotWithShape) [*line 767*]

Function Parameters:

- *string* **\$rotWithShape**

Generate a:gradfill

- **Access** protected

void function CreateTheme1::generateGS(\$pos) [*line 793*]

Function Parameters:

- *string* **\$pos**

Generate a:gs

- **Access** protected

void function CreateTheme1::generateGS2(\$pos) [*line 807*]

Function Parameters:

- *string* **\$pos**

Generate a:gs

- **Access** protected

void function CreateTheme1::generateGSLST() [*line 780*]

Generate a:gslst

- **Access** protected

void function CreateTheme1::generateHLINK() [*line 518*]

Generate a:hlink

- **Access** protected

void function CreateTheme1::generateLATIN([\$typeface = 'cambria']) [*line 578*]

Function Parameters:

- *string* **\$typeface**

Generate a:latin

- **Access** protected

void function CreateTheme1::generateLIGHTRIG(\$rig, \$dir) [line 1132]

Function Parameters:

- *string* **\$rig**
- *string* **\$dir**

Generate a:lightrig

- **Access** protected

void function CreateTheme1::generateLIN(\$ang, \$scaled, \$val) [line 875]

Function Parameters:

- *string* **\$val**
- *string* **\$scaled**
- **\$ang**

Generate a:lin

- **Access** protected

void function CreateTheme1::generateLN(\$w, \$cap, \$cmpd, \$algn) [line 907]

Function Parameters:

- *string* **\$w**
- *string* **\$cap**
- *string* **\$cmpd**
- *string* **\$algn**

Generate a:ln

- **Access** protected

void function CreateTheme1::generateLN2(\$w, \$scap, \$scmpd, \$algn) [*line 925*]

Function Parameters:

- *string* **\$w**
- *string* **\$scap**
- *string* **\$scmpd**
- *string* **\$algn**

Generate a:ln

- **Access** protected

void function CreateTheme1::generateLNSTYLELST() [*line 888*]

Generate a:lnstylelst

- **Access** protected

void function CreateTheme1::generateLT1() [*line 388*]

Generate a:lt1

- **Access** protected

void function CreateTheme1::generateLT2() [*line 427*]

Generate a:lt2

- **Access** protected

void function CreateTheme1::generateMAYORFONT() [*line 562*]

Generate a:mayorfont

- **Access** protected

void function CreateTheme1::generateMINORFONT() [*line 676*]

Generate a:minorfont

- **Access** protected

void function CreateTheme1::generateOBJECTDEFAULTS() [*line 1239*]

Generate a:objectdefaults

- **Access** protected

void function CreateTheme1::generateOUTERSHDW(\$blurRad, \$dist, \$dir, \$rotWithShape) [*line 1031*]

Function Parameters:

- *string* **\$blurRad**
- *string* **\$dist**
- *string* **\$dir**
- *string* **\$rotWithShape**

Generate a:outershdw

- **Access** protected

void function CreateTheme1::generatePATH(\$path) [*line 1207*]

Function Parameters:

- *string* **\$path** @path

Generate a:path

- **Access** protected

void function CreateTheme1::generatePRSTDASH(\$val) [*line 954*]

Function Parameters:

- *string* **\$val**

Generate a:prstdash

- **Access** protected

void function CreateTheme1::generateROT(\$lat, \$lon, \$rev) [*line 1117*]

Function Parameters:

- *string* **\$lat**

- *string* **\$lon**
- *string* **\$rev** @rev

Generate a:rot

- **Access** protected

void function CreateTheme1::generateSATMOD(\$val) [*line 861*]

Function Parameters:

- *string* **\$val**

Generate a:satmod

- **Access** protected

void function CreateTheme1::generateSCENE3D() [*line 1086*]

- **Access** protected

void function CreateTheme1::generateSCHEMECLR(\$val) [*line 737*]

Function Parameters:

- *string* **\$val**

Generate a:schemeclr

- **Access** protected

void function CreateTheme1::generateSCHEMECLR2(\$val) [*line 820*]

Function Parameters:

- *string* \$val

Generate a:schemeclr

- **Access** protected

void function CreateTheme1::generateSCHEMECLR3(\$val) [*line 940*]

Function Parameters:

- *string* \$val

Generate a:schemeclr3

- **Access** protected

void function CreateTheme1::generateSHADE(\$val) [*line 848*]

Function Parameters:

- *string* \$val

Generate a:shade

- **Access** protected

void function CreateTheme1::generateSOLIDFILL() [*line 719*]

Generate a:solidfill

- **Access** protected

void function CreateTheme1::generateSP3D() [*line 1146*]

Generate a:sp3d

- **Access** protected

void function CreateTheme1::generateSRGBCLR([\$val = 'windowText']) [*line 415*]

Function Parameters:

- *string* **\$val**

Generate a:srgbclr

- **Access** protected

void function CreateTheme1::generateSRGBCLR2(\$val) [*line 1047*]

Function Parameters:

- *string* **\$val**

Generate a:srgbclr2

- **Access** protected

void function CreateTheme1::generateSYSCLR([\$val = 'windowText'], [\$lastClr = '000000']) [*line 375*]

Function Parameters:

- *string* **\$val**
- *string* **\$lastClr**

Generate a:sysclr

- **Access** protected

void function CreateTheme1::generateTHEMEELEMENTS() [*line 325*]

Generate a:themeelements

- **Access** protected

void function CreateTheme1::generateTINT(\$val) [*line 834*]

Function Parameters:

- *string* **\$val**

Generate a:tint

- **Access** protected

void function CreateTheme1::generateTINT2(\$val) [*line 1193*]

Function Parameters:

- *string* \$val

Generate a:tint2

- **Access** protected

CreateTheme1 function CreateTheme1::getInstance() [*line 83*]

- **Static**
- **Access** public

void function CreateTheme1::__destruct() [*line 62*]

Destruct

- **Access** public

string function CreateTheme1::__toString() [*line 72*]

- **Access** public

Class CreateWebSettings

[line 29]

Create default websettings XML

- **Package** elements
- **Version** 1.0
- **Copyright** Copyright (c) 2009-2011 Narcea Producciones Multimedia S.L. (http://www.2mdc.com)
- **Link** <http://www.phpdocx.com>
- **Since** Class available since Release 1.0
- **License** http://www.phpdocx.com/wp-content/themes/lightword/pro_license.php

CreateWebSettings::\$_xml

mixed = [line 36]

- **Access** protected

Constructor *void* function CreateWebSettings::__construct() [line 49]

Construct

- **Access** public

void function CreateWebSettings::generateWebSettings() [line 94]

Main tags of websettings XML

- **Access** public

CreateWebSettings function *CreateWebSettings::getInstance()* [*line 81*]
Singleton, return instance of class

- **Static**
- **Access** public

void function *CreateWebSettings::__destruct()* [*line 59*]
Destruct

- **Access** public

string function *CreateWebSettings::__toString()* [*line 70*]
Magic method, returns current XML

- **Access** public

Class *CreateXlsx* [*line 28*]

Create XLSX

- **Package** elements
- **Version** 1.0
- **Copyright** Copyright (c) 2009-2011 Narcea Producciones Multimedia S.L. (<http://www.2mdc.com>)
- **Link** <http://www.phpdocx.com>
- **Since** Class available since Release 1.0
- **License** http://www.phpdocx.com/wp-content/themes/lightword/pro_license.php

Constructor *void* function CreateXlsx::__construct() [*line 67*]

Construct

- **Access** public

void function CreateXlsx::addSharedStrings(\$args[1]) [*line 210*]

Function Parameters:

- *array* **\$args[1]**

Add shared strings

- **Access** protected

void function CreateXlsx::addSheet(\$args[1]) [*line 225*]

Function Parameters:

- *array* **\$args[1]**

Add sheet

- **Access** protected

void function CreateXlsx::addTable(\$args[0], \$args[1]) [*line 195*]

Function Parameters:

- *array* **\$args[0]**
- *array* **\$args[1]**

Add table

- **Access** protected

bool function CreateXlsx::createXlsx() [*line 112*]

Create XLSX

- **Access** public

CreateXlsx function CreateXlsx::getInstance() [*line 98*]

- **Static**
- **Access** public

void function CreateXlsx::__destruct() [*line 77*]

Destruct

- **Access** public

string function CreateXlsx::__toString() [*line 87*]

- **Access** public

Class TransformDoc

[*line 33*]

Transform DOCX to PDF or XHTML

- **Package** elements
- **Version** 1.0
- **Copyright** Copyright (c) 2009-2011 Narcea Producciones Multimedia S.L. (<http://www.2mdc.com>)
- **Link** <http://www.phpdocx.com>
- **Since** Class available since Release 1.0
- **License** http://www.phpdocx.com/wp-content/themes/lightword/pro_license.php

TransformDoc::SCHEMA_IMAGEDOCUMENT

=
'http://schemas.openxmlformats.org/officeDocument/2006/relationships/image' [*line 35*]

TransformDoc::SCHEMA_OFFICEDOCUMENT

=
'http://schemas.openxmlformats.org/officeDocument/2006/relationships/officeDocument' [*line 37*]

Constructor *void* function TransformDoc::__construct() [*line 52*]

Construct

- **Access public**

string function TransformDoc::absoluteZipPath(\$path) [*line 132*]

Function Parameters:

- **\$path**

Return zip path

- **Access public**

void function TransformDoc::cleanXHTML() [*line 156*]

Clean HTML

- **Access public**

void function TransformDoc::generatePDF() [*line 275*]

Convert DOCX to PDF, using dompdf. DOCX->XHTML->PDF

- **Access public**

void function TransformDoc::generateXHTML() [*line 194*]

Convert DOCX to XHTML

- **Access public**

void function TransformDoc::getFileName() [line 176]

Return file name

- **Access public**

void function TransformDoc::getstrFile() [line 72]

Getter. File

- **Access public**

void function TransformDoc::getStrOutputFile() [line 92]

Getter. Output file

- **Access public**

void function TransformDoc::getStrXHTML() [line 82]

Getter. XHTML

- **Access public**

void function TransformDoc::setstrFile(\$file) [line 102]

Function Parameters:

- **\$file**

Setter. File

- **Access public**

void function TransformDoc::setStrOutputFile(\$outputFile) [line 121]

Function Parameters:

- *string* **\$outputFile**

- **Access public**

void function TransformDoc::setStrXHTML(\$strXHTML) [line 112]

Function Parameters:

- **\$strXHTML**

Setter. XHTML

- **Access public**

void function TransformDoc::validatorXHTML() [line 297]

Validate HTML using tidy

- **Access** public

void function TransformDoc::__destruct() [*line 62*]

Destruct

- **Access** public

Package loader Procedural Elements

AutoLoader.inc

Autoloader

- **Package** loader
- **Version** 2.0
- **Copyright** Copyright (c) 2009-2011 Narcea Producciones Multimedia S.L.
(<http://www.2mdc.com>)
- **Link** <http://www.phpdocx.com>
- **Since** File available since Release 2.0
- **License** LGPL

Package loader Classes

Class AutoLoader *[line 28]*

Autoloader

- **Package** loader
- **Version** 2.0
- **Copyright** Copyright (c) 2009-2011 Narcea Producciones Multimedia S.L.
(<http://www.2mdc.com>)
- **Link** <http://www.phpdocx.com>
- **Since** Class available since Release 2.0
- **License** http://www.phpdocx.com/wp-content/themes/lightword/pro_license.php

void function AutoLoader::load() *[line 80]*

Main tags of relationships XML

- **Static**
- **Access** public

void function AutoLoader::loadPDF() *[line 86]*

- **Static**
- **Access** public

Appendices

Appendix A - Class Trees

Package elements

CreateElement

- [CreateElement](#)
 - [CreateChartRels](#)
 - [CreateExcelSharedStrings](#)
 - [CreateExcelSheet](#)
 - [CreateExcelTable](#)
 - [CreateFontTable](#)
 - [CreateFooter](#)
 - [CreateFootnote](#)
 - [CreateGraphic](#)
 - [CreateHeader](#)
 - [CreateImage](#)
 - [CreateLink](#)
 - [CreateList](#)
 - [CreatePage](#)
 - [CreateSettings](#)
 - [CreateStyle](#)
 - [CreateStyleTable](#)
 - [CreateTable](#)
 - [CreateTableContents](#)
 - [CreateText](#)
 - [CreateTheme1](#)
 - [CreateWebSettings](#)

CreateXlsx

- [CreateXlsx](#)

TransformDoc

- [TransformDoc](#)

Package loader

AutoLoader

- [AutoLoader](#)

Package create

CreateDocx

- [CreateDocx](#)

Index

A

AutoLoader::loadPDF()	216
AutoLoader::load()	216
<i>Main tags of relationships XML</i>	
AutoLoader	216
<i>Autoloader</i>	
AutoLoader.inc	215
<i>Autoloader</i>	

C

CreateStyle::generateCOLOR()	145
<i>Generate w:color</i>	
CreateStyle::generateCONTEXTUALSPACING()	145
<i>Generate w:contextualspacing</i>	
CreateStyle::generateI()	145
<i>Generate w:i</i>	
CreateStyle::generateICS()	146
<i>Generate w:ics</i>	
CreateStyle::generateBOTTOM()	144
<i>Generate w:bottom</i>	
CreateStyle::generateBCS()	144
<i>Generate w:bcs</i>	
CreateStyle::generateAUTOREDEFINE()	144
<i>Generate w:autoredefine</i>	
CreateStyle::generateB()	144
<i>Generate w:b</i>	
CreateStyle::generateBASEDON()	144
<i>Generate w:basedon</i>	
CreateStyle::generateLVL()	146
<i>Generate w:lvl</i>	
CreateStyle::generateIND()	146
<i>Generate w:ind</i>	
CreateStyle::generateNAME()	148
<i>Generate w:name</i>	
CreateStyle::generateNEXT()	149
<i>Generate w:next</i>	
CreateStyle::generateNUMPR()	149
<i>Generate w:numpr</i>	
CreateStyle::generateLINK()	148
<i>Generate w:link</i>	
CreateStyle::generateLEFT()	148
<i>Generate w:left</i>	
CreateStyle::generateKEEPLINES()	147

Generate w:keeplines	
CreateStyle::generateKEEPNEXT()	147
Generate w:keepnext	
CreateStyle::generateKERN()	147
Generate w:kern	
CreateStyle::createStyle()	143
Create style	
CreateStyle::addStyleTable()	143
Add table style	
CreatePage::__destruct()	140
Destruct	
CreatePage::__toString()	140
CreateSettings	140
Create default settings	
CreatePage::getInstance()	139
CreatePage::generateTITLEPG()	139
Generate w:titlepg	
CreatePage::generatePGSZ()	138
Generate w:pgsz	
CreatePage::generateSECTIONSECTPR()	138
Generate w:sectionsectpr	
CreatePage::generateSECTPR()	139
Generate w:sectpr	
CreateSettings::\$ xml	140
constructor CreateSettings::__construct()	141
Construct	
CreateStyle::\$ xml	142
constructor CreateStyle::__construct()	142
Construct	
CreateStyle::addStyle()	142
Add style	
CreateStyle	142
Create styles	
CreateSettings::__toString()	141
Magic method, returns current XML	
CreateSettings::generateSettings()	141
Generate settings	
CreateSettings::getInstance()	141
Singleton, return instance of class	
CreateSettings::__destruct()	141
Destruct	
CreateStyle::generateOUTLINELVL()	149
Generate w:outlinelvl	
CreateStyle::generatePBDR()	150
Generate w:pbdpr	
CreateStyle::generateTBLCELLMAR()	159
Generate w:tblcellmar	
CreateStyle::generateTBLIND()	159
Generate w:tblind	
CreateStyle::generateTBLPR()	159
Generate w:tblpr	
CreateStyle::generateTBLSTYLECOLBANDSIZE()	159
Generate w:tblstylecolbandsze	

CreateStyle::generateTBLBORDERS_TOP()	158
<i>Generate w:top</i>	
CreateStyle::generateTBLBORDERS_RIGHT()	158
<i>Generate w:right</i>	
CreateStyle::generateTBLBORDERS_INSIDEH()	156
<i>Generate w:insideh</i>	
CreateStyle::generateTBLBORDERS_INSIDEV()	157
<i>Generate w:insidev</i>	
CreateStyle::generateTBLBORDERS_LEFT()	157
<i>Generate w:left</i>	
CreateStyle::generateTBLSTYLEROWBANDSIZE()	160
<i>Generate w:tblstylerowbandsizesize</i>	
CreateStyle::generateTCPR()	160
<i>Generate w:tcpr</i>	
CreateStyle::getInstance()	162
CreateStyle::destruct()	162
<i>Destruct</i>	
CreateStyle::toString()	162
CreateStyle::generateVERTALIGN()	162
<i>Generate w:vertAlign</i>	
CreateStyle::generateUNHIDEWHENUSED()	161
<i>Generate w:unhidewhenused</i>	
CreateStyle::generateTOP()	160
<i>Generate w:top</i>	
CreateStyle::generateU()	161
<i>Generate w:u</i>	
CreateStyle::generateUIPRIORITY()	161
<i>Generate w:uipriority</i>	
CreateStyle::generateTBLBORDERS_BOTTOM()	156
<i>Generate w:bottom</i>	
CreateStyle::generateTBLBORDERS()	156
<i>Generate w:tblborders</i>	
CreateStyle::generateRIGHT()	151
<i>Generate w:right</i>	
CreateStyle::generateRPR()	152
<i>Generate w:rpr</i>	
CreateStyle::generateRPR_SPACING()	152
<i>Generate w:spacing</i>	
CreateStyle::generateRFONTS2()	151
<i>Generate w:rfonts</i>	
CreateStyle::generateRFONTS()	151
<i>Generate w:rfonts</i>	
CreateStyle::generatePBDR_BOTTOM()	150
<i>Generate w:pbdr</i>	
CreateStyle::generatePPR()	150
<i>Generate w:ppr</i>	
CreateStyle::generateQFORMAT()	150
<i>Generate w:qformat</i>	
CreateStyle::generateRSID()	152
<i>Generate w:rsid</i>	
CreateStyle::generateSEMIHIDDEN()	153
<i>Generate w:semihidden</i>	
CreateStyle::generateTABCENTER()	155

Generate w:tabcenter	
CreateStyle::generateTABRIGHT()	155
Generate w:tabright	
CreateStyle::generateTABS()	155
Generate w:tabs	
CreateStyle::generateSZCS()	154
Generate w:szcs	
CreateStyle::generateSZ()	154
Generate w:sz	
CreateStyle::generateSHD()	153
Generate w:shd	
CreateStyle::generateSPACING()	153
Generate w:spacing	
CreateStyle::generateSTYLE()	154
Generate w:style	
CreatePage::generatePGMAR()	138
Generate w:pgmar	
CreatePage::generatePageBreak()	137
Gnerate pagebreak	
CreateImage::NAMESPACEWORD1	123
CreateImage::NAMESPACEWORD2	123
CreateImage::TAMBORDER	123
constructor CreateImage:: construct()	123
Construct	
CreateImage::NAMESPACEWORD	123
CreateImage::CONSTWORD	123
CreateHeader:: _destruct()	122
Destruct	
CreateHeader:: _toString()	122
CreateImage	122
Create images	
CreateImage::createImage()	123
Create image	
CreateImage::getInstance()	124
CreateImage:: _toString()	125
CreateLink	125
Create links using text strings	
constructor CreateLink:: _construct()	126
Construct	
CreateImage:: _destruct()	125
Destruct	
CreateImage::setRId()	125
Setter. Rid	
CreateImage::getName()	124
Getter. Name	
CreateImage::getRId()	124
Getter. Rid	
CreateImage::setName()	124
Setter. Name	
CreateHeader::getInstance()	122
CreateHeader::generateP()	122
Generate w:p	
CreateGraphic::getInstance()	118

CreateGraphic::getName()	118
<i>Getter. Name</i>	
CreateGraphic::getRId()	118
<i>Getter. Rid</i>	
CreateGraphic::generateVARYCOLORS()	118
<i>Generate w:varyColors</i>	
CreateGraphic::generateVALAX()	118
<i>Generate w:valAx</i>	
CreateGraphic::generateTX()	117
<i>Generate w:tx</i>	
CreateGraphic::generateV()	117
<i>Generate w:v</i>	
CreateGraphic::generateVAL()	117
<i>Generate w:val</i>	
CreateGraphic::getXmlChart()	119
<i>Getter. Xml chart</i>	
CreateGraphic::setName()	119
<i>Setter. Name</i>	
constructor CreateHeader::__construct()	121
<i>Construct</i>	
CreateHeader::createHeader()	121
<i>Create header</i>	
CreateHeader::generateHDR()	121
<i>Generate hdr token</i>	
CreateHeader	120
<i>Create header</i>	
CreateGraphic::__toString()	120
CreateGraphic::setRId()	119
<i>Setter. Rid</i>	
CreateGraphic::setXmlChart()	120
<i>Setter. Xml chart</i>	
CreateGraphic::__destruct()	120
<i>Destruct</i>	
CreateLink::createLink()	126
<i>Create a link</i>	
CreateLink::generateFLDCHAR()	126
<i>Generate w:fldChar</i>	
CreateList::getInstance()	134
CreateList::runArray()	134
<i>Recursive generation of lists</i>	
CreateList::__destruct()	134
<i>Destruct</i>	
CreateList::generatePSTYLE()	133
<i>Generate w:pstyle</i>	
CreateList::generateNUMPR()	133
<i>Generate w:numpr</i>	
CreateList::generateILVL()	132
<i>Generate w:ilvl</i>	
CreateList::generateLISTPR()	132
<i>Generate w:listpr</i>	
CreateList::generateNUMID()	133
<i>Generate w:numid</i>	
CreateList::__toString()	134

CreatePage	135
<i>Create pages</i>	
CreatePage::generateCOL()	136
<i>Generate w:col</i>	
CreatePage::generateCOLS()	137
<i>Generate w:cols</i>	
CreatePage::generateDOCGRID()	137
<i>Generate w:docgrid</i>	
CreatePage::generateBR()	136
<i>Generate w:br</i>	
CreatePage::createSECTPR()	136
<i>Create sectpr</i>	
CreatePage::\$xml	135
constructor CreatePage::__construct()	135
<i>Construct</i>	
CreatePage::createPage()	135
<i>Create page</i>	
CreateList::generateILFO()	132
<i>Generate w:ilfo</i>	
CreateList::createList()	131
<i>Create list</i>	
CreateLink::getFont()	128
<i>Getter. Access to font var</i>	
CreateLink::getInstance()	128
<i>Singleton, return instance of class</i>	
CreateLink::getLink()	129
<i>Getter. Access to link var</i>	
CreateLink::generateRSTYLE()	128
<i>Generate w:rStyle</i>	
CreateLink::generateR()	128
<i>Generate w:r</i>	
CreateLink::generateHYPERLINK()	127
<i>Generate w:hyperlink</i>	
CreateLink::generateINSTRTEXT()	127
<i>Generate w:instrText</i>	
CreateLink::generatePROOFERR()	127
<i>Generate w:proofErr</i>	
CreateLink::getTitle()	129
<i>Getter. Access to title var</i>	
CreateLink::__destruct()	129
<i>Destruct</i>	
CreateList::\$val	131
constructor CreateList::__construct()	131
<i>Construct</i>	
CreateList::addList()	131
<i>Add list</i>	
CreateList::\$list	130
CreateList::\$font	130
CreateLink::__toString()	129
<i>Magic method, returns current XML</i>	
CreateList	130
<i>Create lists</i>	
CreateList::\$data	130

CreateStyleTable	163
<i>Create style table</i>	
CreateStyleTable::\$ xml	163
CreateTheme1::generateGRADFILL2()	194
<i>Generate a:gradfill</i>	
CreateTheme1::generateGS()	194
<i>Generate a:gs</i>	
CreateTheme1::generateGS2()	194
<i>Generate a:gs</i>	
CreateTheme1::generateGSLST()	195
<i>Generate a:gslst</i>	
CreateTheme1::generateGRADFILL()	193
<i>Generate a:gradfill</i>	
CreateTheme1::generateFONTSCHEMA()	193
<i>Generate a:fontschema</i>	
CreateTheme1::generateFONT()	192
<i>Generate a:font</i>	
CreateTheme1::generateFONT2()	192
<i>Generate a:font</i>	
CreateTheme1::generateFONT3()	193
<i>Generate a:font</i>	
CreateTheme1::generateHLINK()	195
<i>Generate a:hlink</i>	
CreateTheme1::generateLATIN()	195
<i>Generate a:latin</i>	
CreateTheme1::generateLT1()	197
<i>Generate a:lt1</i>	
CreateTheme1::generateLT2()	197
<i>Generate a:lt2</i>	
CreateTheme1::generateMAYORFONT()	198
<i>Generate a:mayorfont</i>	
CreateTheme1::generateLNSTYLELST()	197
<i>Generate a:lnstylelst</i>	
CreateTheme1::generateLN2()	197
<i>Generate a:ln</i>	
CreateTheme1::generateLIGHTRIG()	196
<i>Generate a:lightrig</i>	
CreateTheme1::generateLIN()	196
<i>Generate a:lin</i>	
CreateTheme1::generateLN()	196
<i>Generate a:ln</i>	
CreateTheme1::generateFOLHLINK()	192
<i>Generate a:folhlink</i>	
CreateTheme1::generateFMTSCHEME()	191
<i>Generate a:fmtscheme</i>	
CreateTheme1::generateCLRScheme()	188
<i>Generate a:clrscheme</i>	
CreateTheme1::generateCS()	188
<i>Generate a:cs</i>	
CreateTheme1::generateDK1()	189
<i>Generate a:dk1</i>	
CreateTheme1::generateCAMERA()	188
<i>Generate a:camera</i>	

CreateTheme1::generateBGFILLSTYLELST()	188
<i>Generate a:bgfillstylelst</i>	
CreateTheme1::generateACCENT6()	187
<i>Generate a:accent6</i>	
CreateTheme1::generateALPHA()	187
<i>Generate a:alpha</i>	
CreateTheme1::generateBEVELT()	187
<i>Generate a:bevelt</i>	
CreateTheme1::generateDK2()	189
<i>Generate a:dk2</i>	
CreateTheme1::generateEA()	189
<i>Generate a:ea</i>	
CreateTheme1::generateEXTRACLRSchemeLST()	191
<i>Generate a:extraclrschemelst</i>	
CreateTheme1::generateFILLSTYLELST()	191
<i>Generate a:fillstylelst</i>	
CreateTheme1::generateFILLTORECT()	191
<i>Generate a:filltoirect</i>	
CreateTheme1::generateEFFECTSTYLELST()	190
<i>Generate a:effectstylest</i>	
CreateTheme1::generateEFFECTSTYLE2()	190
<i>Generate a:effectstyle2</i>	
CreateTheme1::generateEFFECTLST()	190
<i>Generate a:effectlst</i>	
CreateTheme1::generateEFFECTLST2()	190
<i>Generate a:effectlst2</i>	
CreateTheme1::generateEFFECTSTYLE()	190
<i>Generate a:effectstyle</i>	
CreateTheme1::generateMINORFONT()	198
<i>Generate a:minorfont</i>	
CreateTheme1::generateOBJECTDEFAULTS()	198
<i>Generate a:objectdefaults</i>	
CreateWebSettings::getInstance()	206
<i>Singleton, return instance of class</i>	
CreateWebSettings::destruct()	206
<i>Destruct</i>	
CreateWebSettings::toString()	206
<i>Magic method, returns current XML</i>	
CreateWebSettings::generateWebSettings()	205
<i>Main tags of websettings XML</i>	
constructor CreateWebSettings::construct()	205
<i>Construct</i>	
CreateTheme1::toString()	204
CreateWebSettings	205
<i>Create default websettings XML</i>	
CreateWebSettings::\$xml	205
CreateXlsx	206
<i>Create XLSX</i>	
constructor CreateXlsx::construct()	207
<i>Construct</i>	
CreateXlsx::destruct()	208
<i>Destruct</i>	
CreateXlsx::toString()	209

constructor TransformDoc:: construct()	209
<i>Construct</i>	
CreateXlsx::getInstance()	208
CreateXlsx::createXlsx()	208
<i>Create XLSX</i>	
CreateXlsx::addSharedStrings()	207
<i>Add shared strings</i>	
CreateXlsx::addSheet()	207
<i>Add sheet</i>	
CreateXlsx::addTable()	208
<i>Add table</i>	
CreateTheme1:: destruct()	204
<i>Destruct</i>	
CreateTheme1::getInstance()	204
CreateTheme1::generateSCENE3D()	200
CreateTheme1::generateSCHEMECLR()	200
<i>Generate a:schemeclr</i>	
CreateTheme1::generateSCHEMECLR2()	201
<i>Generate a:schemeclr</i>	
CreateTheme1::generateSATMOD()	200
<i>Generate a:satmod</i>	
CreateTheme1::generateROT()	199
<i>Generate a:rot</i>	
CreateTheme1::generateOUTERSHDW()	198
<i>Generate a:outershdw</i>	
CreateTheme1::generatePATH()	199
<i>Generate a:path</i>	
CreateTheme1::generatePRSTDASH()	199
<i>Generate a:prstdash</i>	
CreateTheme1::generateSCHEMECLR3()	201
<i>Generate a:schemeclr3</i>	
CreateTheme1::generateSHADE()	201
<i>Generate a:shade</i>	
CreateTheme1::generateTHEMEELEMENTS()	203
<i>Generate a:themeelements</i>	
CreateTheme1::generateTINT()	203
<i>Generate a:tint</i>	
CreateTheme1::generateTINT2()	204
<i>Generate a:tint2</i>	
CreateTheme1::generateSYSCLR()	203
<i>Generate a:sysclr</i>	
CreateTheme1::generateSRGBCLR2()	202
<i>Generate a:srgbclr2</i>	
CreateTheme1::generateSOLIDFILL()	202
<i>Generate a:solidfill</i>	
CreateTheme1::generateSP3D()	202
<i>Generate a:sp3d</i>	
CreateTheme1::generateSRGBCLR()	202
<i>Generate a:srgbclr</i>	
CreateTheme1::generateACCENT5()	186
<i>Generate a:accent5</i>	
CreateTheme1::generateACCENT4()	186
<i>Generate a:accent4</i>	

CreateTable::generateTBLINSIDEV()	171
<i>Generate w:tblinsidev</i>	
CreateTable::generateTBLLEFT()	171
<i>Generate w:tblleft</i>	
CreateTable::generateTBLLOOK()	171
<i>Generate w:tbllook</i>	
CreateTable::generateTBLOVERLAP()	172
<i>Generate w:tbloverlap</i>	
CreateTable::generateTBLINSIDEH()	170
<i>Generate w:tblinsideh</i>	
CreateTable::generateTBLGRID()	170
<i>Generate w:tblgrid</i>	
CreateTable::generateTBLBORDERS()	169
<i>Generate w:tblborders</i>	
CreateTable::generateTBLBOTTOM()	169
<i>Generate w:tblbottom</i>	
CreateTable::generateTBLCELLSPACING()	170
<i>Generate w:tblcellspacing</i>	
CreateTable::generateTBLPR()	172
<i>Generate w:tblpr</i>	
CreateTable::generateTBLRIGHT()	172
<i>Generate w:tblright</i>	
CreateTable::generateTCW()	174
<i>Generate w:tcw</i>	
CreateTable::generateTR()	175
<i>Generate w:tr</i>	
CreateTable::generateTRPR()	175
<i>Generate w:trpr</i>	
CreateTable::generateTCPR()	174
<i>Generate w:tcpr</i>	
CreateTable::generateTC()	174
<i>Generate w:tc</i>	
CreateTable::generateTBLSTYLE()	173
<i>Generate w:tblstyle</i>	
CreateTable::generateTBLTOP()	173
<i>Generate w:tbltop</i>	
CreateTable::generateTBLW()	173
<i>Generate w:tblw</i>	
CreateTable::generateTBL()	169
<i>Generate w:tbl</i>	
CreateTable::generateSHD()	168
<i>Generate w:shd</i>	
CreateStyleTable::generateTCBORDERS()	165
<i>Generate w:tcBorders</i>	
CreateStyleTable::generateTCPR()	165
<i>Generate w:tcPr</i>	
CreateStyleTable::getInstance()	165
CreateStyleTable::generateTBLSTYLEPR()	164
<i>Generate w:tblStylePr</i>	
CreateStyleTable::generateTBLPR()	164
<i>Generate w:tblPr</i>	
constructor CreateStyleTable::__construct()	163
<i>Construct</i>	

CreateStyleTable::addStyleTable()	163
<i>Add table style</i>	
CreateStyleTable::generateSHD()	164
<i>Generate w:shd</i>	
CreateStyleTable::__destruct()	165
<i>Destruct</i>	
CreateStyleTable::__toString()	165
CreateTable::generateHMERGE()	167
<i>Generate w:hmerge</i>	
CreateTable::generateJC()	168
<i>Generate w:jc</i>	
CreateTable::generateP()	168
<i>Generate w:p</i>	
CreateTable::generateGRIDCOLS()	167
<i>Generate w:gridcols</i>	
CreateTable::createTable()	167
<i>Create table</i>	
CreateTable	166
<i>Create tables</i>	
constructor CreateTable::__construct()	166
<i>Construct</i>	
CreateTable::addList()	166
<i>Add list</i>	
CreateTable::generateVMERGE()	175
<i>Generate w:vmerge</i>	
CreateTable::getInstance()	175
CreateText::generateWIDOWCONTROL()	183
<i>Generate w:widowcontrol</i>	
CreateText::generateWORDWRAP()	183
<i>Generate w:wordwrap</i>	
CreateText::getInstance()	184
<i>Singleton, return instance of class</i>	
CreateText::generateU()	183
<i>Generate w:u</i>	
CreateText::generateSZ()	182
<i>Generate w:sz</i>	
CreateText::generateJC()	181
<i>Generate w:jc</i>	
CreateText::generatePAGEBREAKBEFORE()	182
<i>Generate w:pagebreakbefore</i>	
CreateText::generatePSTYLE()	182
<i>Generate w:pstyle</i>	
CreateText::__destruct()	184
<i>Destruct</i>	
CreateText::__toString()	184
<i>Magic method, returns current XML</i>	
CreateTheme1::generateACCENT1()	186
<i>Generate a:accent1</i>	
CreateTheme1::generateACCENT2()	186
<i>Generate a:accent2</i>	
CreateTheme1::generateACCENT3()	186
<i>Generate a:accent3</i>	
CreateTheme1::createTheme()	185

<i>Create theme</i>	
constructor CreateTheme1:: <u>construct()</u>	185
<i>Construct</i>	
CreateTheme1	184
CreateTheme1::NAMESPACEWORD	185
CreateTheme1::\$ <u>xml</u>	185
CreateText::<u>generateI()</u>	181
<i>Generate w:i</i>	
CreateText::<u>generateCOLOR()</u>	181
<i>Generate w:color</i>	
CreateTableContents::<u>createTableContents()</u>	177
<i>Create table of contents</i>	
CreateTableContents::<u>generateFLDSIMPLE()</u>	177
<i>Generate w:fldsimple</i>	
CreateTableContents::<u>getInstance()</u>	177
constructor CreateTableContents:: <u>construct()</u>	177
<i>Construct</i>	
CreateTableContents::\$ <u>xml</u>	176
CreateTable:: <u>destruct()</u>	175
<i>Destruct</i>	
CreateTable:: <u>toString()</u>	176
CreateTableContents	176
<i>Create table of contents</i>	
CreateTableContents:: <u>destruct()</u>	178
<i>Destruct</i>	
CreateTableContents:: <u>toString()</u>	178
<i>Magic method, returns current XML</i>	
CreateText::<u>generateB()</u>	179
<i>Generate w:b</i>	
CreateText::<u>generateBOOKMARKEND()</u>	180
<i>Generate w:bookmarkend</i>	
CreateText::<u>generateBOOKMARKSTART()</u>	180
<i>Generate w:bookmarkstart</i>	
CreateText::<u>createTitle()</u>	179
<i>Create title</i>	
CreateText::<u>createText()</u>	179
<i>Create text</i>	
CreateText	178
<i>Create text</i>	
CreateText::<u>IDTITLE</u>	179
constructor CreateText:: <u>construct()</u>	179
<i>Destruct</i>	
CreateGraphic::<u>generateTITLETX()</u>	117
<i>Generate w:titletx</i>	
CreateGraphic::<u>generateTITLET()</u>	116
<i>Generate w:titlet</i>	
CreateChartRels:: <u>toString()</u>	54
<i>Magic method, returns current XML</i>	
CreateElement	54
<i>Main class, create tag elements</i>	
CreateElement::<u>MATHNAMESPACEWORD</u>	55
CreateElement::<u>NAMESPACEWORD</u>	55
CreateChartRels:: <u>destruct()</u>	54

<i>Destruct</i>	
CreateChartRels::getInstance()	54
<i>Singleton, return instance of class</i>	
CreateChartRels::createRelationship()	53
<i>Create relationship document to use in DOCX file</i>	
CreateChartRels::generateRELATIONSHIP()	53
<i>New relationship, added to relationships XML</i>	
CreateChartRels::generateRELATIONSHIPS()	53
<i>Main tags of relationships XML</i>	
CreateElement::\$ _xml	55
constructor CreateElement:: _construct()	55
<i>Construct</i>	
CreateElement::generateBCS()	57
<i>Generate w:bcs</i>	
CreateElement::generateBLIP()	57
<i>Generate w:blip</i>	
CreateElement::generateBLIPFILL()	57
<i>Generate w:blipfill</i>	
CreateElement::generateB()	56
<i>Generate w:b</i>	
CreateElement::generateAVLST()	56
<i>Generate w:avlst</i>	
CreateElement::cleanTemplate()	55
<i>Delete pending tags</i>	
CreateElement::cleanTemplateFirstRPR()	55
<i>Delete first w:rpr</i>	
CreateElement::generateANCHOR()	56
<i>Generate w:anchor</i>	
constructor CreateChartRels:: _construct()	52
<i>Construct</i>	
CreateChartRels::\$ _xml	52
CreateLink.inc	39
<i>Create links using text strings</i>	
CreateList.inc	40
<i>Create lists</i>	
CreatePage.inc	41
<i>Create pages</i>	
CreateImage.inc	38
<i>Create images</i>	
CreateHeader.inc	37
<i>Create header</i>	
CreateFooter.inc	34
<i>Create footer</i>	
CreateFootnote.inc	35
<i>Create footnote</i>	
CreateGraphic.inc	36
<i>Create graphics (charts)</i>	
CreateSettings.inc	42
<i>Create default settings</i>	
CreateStyle.inc	43
<i>Create styles</i>	
CreateWebSettings.inc	49
<i>Create default websettings XML</i>	

CreateXlsx.inc	50
<i>Create XLSX</i>	
CreateChartRels	52
<i>Create relationships used by images, charts...</i>	
CreateTheme1.inc	48
CreateText.inc	47
<i>Create text</i>	
CreateStyleTable.inc	44
<i>Create style table</i>	
CreateTable.inc	45
<i>Create tables</i>	
CreateTableContents.inc	46
<i>Create table of contents</i>	
CreateElement::generateCNVGRAPHICFRAMEPR()	57
<i>Generate w:cnvgraphicframepr</i>	
CreateElement::generateCNVPICPR()	58
<i>Generate w:cnvpicpr</i>	
CreateElement::generatePSTYLE()	66
<i>Generate w:pstyle</i>	
CreateElement::generateQUITAR()	66
<i>Generate w:r</i>	
CreateElement::generaterR()	67
<i>Generate w:r</i>	
CreateElement::generatePRSTGEOM()	66
<i>Generate w:prstgeom</i>	
CreateElement::generatePRSTDASH()	65
<i>Generate w:prstdash</i>	
CreateElement::generatePOSITIONV()	64
<i>Generate w:positionv</i>	
CreateElement::generatePOSOFFSET()	65
<i>Generate w:posoffset</i>	
CreateElement::generatePPR()	65
<i>Generate w:ppr</i>	
CreateElement::generateRFONTS()	67
<i>Generate w:rfonts</i>	
CreateElement::generateRPR()	67
<i>Generate w:rpr</i>	
CreateElement::generateSTART()	69
<i>Generate w:start</i>	
CreateElement::generateSTRETCH()	69
<i>Generate w:stretch</i>	
CreateElement::generateT()	69
<i>Generate w:t</i>	
CreateElement::generateSPPR()	69
<i>Generate w:sppr</i>	
CreateElement::generateSOLIDFILL()	68
<i>Generate w:solidfill</i>	
CreateElement::generateRSTYLE()	67
<i>Generate w:rstyle</i>	
CreateElement::generateSCHEMECLR()	68
<i>Generate w:schemeclr</i>	
CreateElement::generateSIMPLEPOS()	68
<i>Generate w:simplepos</i>	

CreateElement::generatePOSITIONH()	64
<i>Generate w:positionh</i>	
CreateElement::generatePIC()	64
<i>Generate w:pic</i>	
CreateElement::generateEXTENT()	60
<i>Generate w:extent</i>	
CreateElement::generateFILLRECT()	60
<i>Generate w:fillrect</i>	
CreateElement::generateGRAPHIC()	60
<i>Generate w:graphic</i>	
CreateElement::generateEXT()	59
<i>Generate w:ext</i>	
CreateElement::generateEFFECTEXTENT()	59
<i>Generate w:effectextent</i>	
CreateElement::generateCNVPR()	58
<i>Generate w:cnvpr</i>	
CreateElement::generateDOCPR()	58
<i>Generate w:docpr</i>	
CreateElement::generateDRAWING()	59
<i>Generate w:drawing</i>	
CreateElement::generateGRAPHICDATA()	61
<i>Generate w:graphicdata</i>	
CreateElement::generateGRAPHICPRAMELOCKS()	61
<i>Generate w:graphicpramelocks</i>	
CreateElement::generateNVPICPR()	63
<i>Generate w:nvpicpr</i>	
CreateElement::generateOFF()	63
<i>Generate w:off</i>	
CreateElement::generateP()	63
<i>Generate w:p</i>	
CreateElement::generateNOPROOF()	63
<i>Generate w:noproof</i>	
CreateElement::generateLN()	62
<i>Generate w:ln</i>	
CreateElement::generateINLINE()	61
<i>Generate w:inline</i>	
CreateElement::generateJC()	62
<i>Generate w:jc</i>	
CreateElement::generateLINETO()	62
<i>Generate w:lineto</i>	
CreateFontTable.inc	33
<i>Create font table</i>	
CreateExcelTable.inc	32
<i>Create excel table</i>	
CreateDocx::fAddBreak()	11
<i>Add a break</i>	
CreateDocx::fAddFont()	11
<i>Add a new font</i>	
CreateDocx::fAddFooter()	11
<i>Add a footer</i>	
CreateDocx::fAddGraphic()	12
<i>Add a graphic</i>	
CreateDocx::createDocx()	10

Generate a new DOCX file	10
CreateDocx::addTitle()	10
Add a title	
CreateDocx::addTable()	9
Add a table.	
CreateDocx::addTableContents()	9
Add a table of contents (TOC)	
CreateDocx::addText()	9
Add a text	
CreateDocx::fAddHeader()	12
Add a header.	
CreateDocx::fAddImage()	12
Add an image	
CreateDocx::fAddTable()	15
Add a table.	
CreateDocx::fAddTableContents()	15
Add a table of contents (TOC)	
CreateDocx::fAddText()	15
Add a text	
CreateDocx::fAddParagraph()	14
Add a paragraph	
CreateDocx::fAddMathEq()	14
Add an existing math eq to DOCX	
CreateDocx::fAddLink()	13
Add a link	
CreateDocx::fAddList()	13
Add a list	
CreateDocx::fAddMathDocx()	14
Convert a math eq to DOCX	
CreateDocx::addParagraph()	8
Add a paragraph	
CreateDocx::addMathEq()	8
Add an existing math eq to DOCX	
CreateDocx::\$graphicTemplate	4
CreateDocx::\$intIdWord	4
CreateDocx::\$log	4
CreateDocx::\$fileGraphicTemplate	3
CreateDocx::SCHEMA_OFFICEDOCUMENT	3
CreateDocx	3
Main class. Methods and vars to generate a DOCX file	
CreateDocx::NAMESPACEWORD	3
CreateDocx::SCHEMA_IMAGEDOCUMENT	3
constructor CreateDocx::construct()	4
Construct	
CreateDocx::addBreak()	5
Add a break	
CreateDocx::addLink()	7
Add a link	
CreateDocx::addList()	7
Add a list	
CreateDocx::addMathDocx()	8
Convert a math eq to DOCX	
CreateDocx::addImage()	6

<i>Add an image</i>	
CreateDocx::addHeader()	6
<i>Add a header.</i>	
CreateDocx::addFont()	5
<i>Add a new font</i>	
CreateDocx::addFooter()	5
<i>Add a footer</i>	
CreateDocx::addGraphic()	6
<i>Add a graphic</i>	
CreateDocx::fAddTitle()	16
<i>Add a title</i>	
CreateDocx::fCreateDocx()	16
<i>Generate a new DOCX file</i>	
CreateDocx::setXmlWordFooter1()	23
<i>Setter</i>	
CreateDocx::setXmlWordHeader1()	24
<i>Setter</i>	
CreateDocx::setXmlWordRelsDocumentRels()	24
<i>Setter</i>	
CreateDocx::setXmlWordFontTable()	23
<i>Setter</i>	
CreateDocx::setXmlWordEndnotes()	23
<i>Setter</i>	
CreateDocx::setXmlDocPropsCore()	22
<i>Setter</i>	
CreateDocx::setXmlRelsRels()	22
<i>Setter</i>	
CreateDocx::setXmlWordDocument()	22
<i>Setter</i>	
CreateDocx::setXmlWordSettings()	24
<i>Setter</i>	
CreateDocx::setXmlWordStyles()	25
<i>Setter</i>	
CreateElement.inc	29
<i>Create tag elements</i>	
CreateExcelSharedStrings.inc	30
<i>Generate excel shared strings</i>	
CreateExcelSheet.inc	31
<i>Create excel sheet</i>	
CreateChartRels.inc	28
<i>Create relationships used by images, charts...</i>	
CreateDocx::__toString()	26
<i>Magic method, returns current word XML</i>	
CreateDocx::setXmlWordThemeTheme1()	25
<i>Setter</i>	
CreateDocx::setXmlWordWebSettings()	25
<i>Setter</i>	
CreateDocx::__destruct()	26
<i>Destruct</i>	
CreateDocx::setXmlDocPropsApp()	21
<i>Setter</i>	
CreateDocx::setXmlContentTypes()	21
<i>Setter</i>	

CreateDocx::getXmlWordDocumentContent()	18
<i>Getter</i>	
CreateDocx::getXmlWordEndnotes()	18
<i>Getter</i>	
CreateDocx::getXmlWordFontTable()	18
<i>Getter</i>	
CreateDocx::getXmlRels_Rels()	18
<i>Getter</i>	
CreateDocx::getXmlDocPropsCore()	17
<i>Getter</i>	
CreateDocx::fSetDefaultFont()	17
<i>Change the default font</i>	
CreateDocx::getXmlContentTypes()	17
<i>Getter</i>	
CreateDocx::getXmlDocPropsApp()	17
<i>Getter</i>	
CreateDocx::getXmlWordFooter1()	18
<i>Getter</i>	
CreateDocx::getXmlWordHeader1()	19
<i>Getter</i>	
CreateDocx::setDefaultFont()	20
<i>Change the default font</i>	
CreateDocx::setEncodeUTF8()	20
<i>Transform to UTF-8 charset</i>	
CreateDocx::setLanguage()	21
<i>Change default language.</i>	
CreateDocx::getXmlWordWebSettings()	20
<i>Setter</i>	
CreateDocx::getXmlWordThemeTheme1()	20
<i>Getter</i>	
CreateDocx::getXmlWordRelsDocumentRels()	19
<i>Getter</i>	
CreateDocx::getXmlWordSettings()	19
<i>Getter</i>	
CreateDocx::getXmlWordStyles()	19
<i>Getter</i>	
CreateElement::generateWRAPNONE()	70
<i>Generate w:wrapnone</i>	
CreateElement::generateWRAPPOLYGON()	70
<i>Generate w:wrappolygon</i>	
CreateGraphic::generateCHARTSPACE()	101
<i>Generate chartspace XML</i>	
CreateGraphic::generateCROSSAX()	101
<i>Generate w:crossAx</i>	
CreateGraphic::generateCROSSBETWEEN()	101
<i>Generate w:crossBetween</i>	
CreateGraphic::generateCROSSES()	102
<i>Generate w:crosses</i>	
CreateGraphic::generateCHART()	101
<i>Generate w:chart</i>	
CreateGraphic::generateCATAX()	100
<i>Generate w:catAx</i>	
CreateGraphic::generateBARDIR()	100

Generate w:barDir	
CreateGraphic::generateBODYPR()	100
Generate w:bodypr	
CreateGraphic::generateCAT()	100
Generate w:cat	
CreateGraphic::generateDATE1904()	102
Generate w:date1904	
CreateGraphic::generateDEFRPR()	102
Generate w:defrpr	
CreateGraphic::generateFORMATCODE()	104
Generate w:formatCode	
CreateGraphic::generateGROUPING()	104
Generate w:grouping	
CreateGraphic::generateIDX()	105
Generate w:idx	
CreateGraphic::generateFIRSTSLICEANG()	104
Generate w:firstSliceAng	
CreateGraphic::generateF()	103
Generate w:f	
CreateGraphic::generateDLBLS()	103
Generate w:dLbIs	
CreateGraphic::generateDOCUMENTCHART()	103
Generate w:chart	
CreateGraphic::generateEXTERNALDATA()	103
Generate w:externalData	
CreateGraphic::generateBARCHART()	99
Generate w:barChart	
CreateGraphic::generateAXPOS()	99
Generate w:axPos	
CreateFootnote::__destruct()	95
Destruct	
CreateFootnote::__toString()	96
CreateGraphic	96
Create graphics (charts)	
CreateFootnote::getInstance()	95
CreateFootnote::generateSPACING()	95
Generate w:spacing	
CreateFootnote::generatePPR()	94
Generate w:ppr	
CreateFootnote::generateR()	94
Generate w:r	
CreateFootnote::generateSEPARATOR()	95
Generate w:separator	
CreateGraphic::NAMESPACEWORD	96
CreateGraphic::\$xmlChart	96
CreateGraphic::generateAUTOTITLEDELETED()	98
Generate w:autotitledeleted	
CreateGraphic::generateAXAXID()	98
Generate w:axId	
CreateGraphic::generateAXID()	99
Generate w:axid	
CreateGraphic::generateAUTO()	98
Generate w:auto	

CreateGraphic::createGraphic()	97
<i>Create graphic</i>	
constructor CreateGraphic::__construct()	96
<i>Construct</i>	
CreateGraphic::createCHARTXML()	97
<i>Create chart xml</i>	
CreateGraphic::createDOCUEMNTXML()	97
<i>Create document xml</i>	
CreateGraphic::generateLANG()	105
<i>Generate w:lang</i>	
CreateGraphic::generateLAYOUT()	105
<i>Generate w:layout</i>	
CreateGraphic::generateSHOWPERCENT()	113
<i>Generate w:showPercent</i>	
CreateGraphic::generateSPPR()	113
<i>Generate w:spPr</i>	
CreateGraphic::generateSTRCACHE()	113
<i>Generate w:strcache</i>	
CreateGraphic::generateSHAPE()	112
<i>Generate w:shape</i>	
CreateGraphic::generateSER()	112
<i>Generate w:ser</i>	
CreateGraphic::generatePTCOUNT()	111
<i>Generate w:ptcount</i>	
CreateGraphic::generateRICH()	112
<i>Generate w:rich</i>	
CreateGraphic::generateSCALING()	112
<i>Generate w:scaling</i>	
CreateGraphic::generateSTRREF()	113
<i>Generate w:strref</i>	
CreateGraphic::generateSTYLE()	114
<i>Generate w:style</i>	
CreateGraphic::generateTITLER()	115
<i>Generate w:titler</i>	
CreateGraphic::generateTITLERFONTS()	115
<i>Generate w:titlerfonts</i>	
CreateGraphic::generateTITLERPR()	116
<i>Generate w:titlerpr</i>	
CreateGraphic::generateTITLEPPR()	115
<i>Generate w:titleppr</i>	
CreateGraphic::generateTITLEP()	115
<i>Generate w:titlep</i>	
CreateGraphic::generateTICKLBLPOS()	114
<i>Generate w:tickLblPos</i>	
CreateGraphic::generateTITLE()	114
<i>Generate w:title</i>	
CreateGraphic::generateTITLELAYOUT()	115
<i>Generate w:titlelayout</i>	
CreateGraphic::generatePT()	111
<i>Generate w:pt</i>	
CreateGraphic::generatePLOTVISONLY()	111
<i>Generate w:poltVisOnly</i>	
CreateGraphic::generateLINECHART()	107

Generate <i>w:lineChart</i>	
CreateGraphic::generateLN()	108
Generate <i>w:ln</i>	
CreateGraphic::generateLSTSTYLE()	108
Generate <i>w:lststyle</i>	
CreateGraphic::generateLEGENDPOS()	107
Generate <i>w:legendPos</i>	
CreateGraphic::generateLEGENDFONT()	107
Generate <i>c:layout</i>	
CreateGraphic::generateLBLALGN()	106
Generate <i>w:lblAlign</i>	
CreateGraphic::generateLBLOFFSET()	106
Generate <i>w:lblOffset</i>	
CreateGraphic::generateLEGEND()	106
Generate <i>w:legend</i>	
CreateGraphic::generateMAJORGRIDLINES()	108
Generate <i>w:majorGridlines</i>	
CreateGraphic::generateNOFILL()	108
Generate <i>w:noFill</i>	
CreateGraphic::generateOVERLAP()	110
Generate <i>w:overlap</i>	
CreateGraphic::generatePIECHART()	110
Generate <i>w:piechart</i>	
CreateGraphic::generatePLOTAREA()	110
Generate <i>w:plotarea</i>	
CreateGraphic::generateORIENTATION()	109
Generate <i>w:orientation</i>	
CreateGraphic::generateORDER()	109
Generate <i>w:order</i>	
CreateGraphic::generateNUMCACHE()	108
Generate <i>w:numcache</i>	
CreateGraphic::generateNUMFMT()	109
Generate <i>w:numFmt</i>	
CreateGraphic::generateNUMREF()	109
Generate <i>w:numRef</i>	
CreateFootnote::generateP()	94
Generate <i>w:p</i>	
CreateFootnote::generateFOOTNOTEREFERENCE()	93
Generate <i>w:footnotereference</i>	
CreateExcelSheet::generateSELECTION()	78
Generate <i>selection</i>	
CreateExcelSheet::generateSHEETDATA()	78
Generate <i>sheetdata</i>	
CreateExcelSheet::generateSHEETFORMATPR()	78
Generate <i>sheetformatpr</i>	
CreateExcelSheet::generateSHEETVIEW()	79
Generate <i>sheetview</i>	
CreateExcelSheet::generateROW()	77
Generate <i>row</i>	
CreateExcelSheet::generatePAGESETUP()	77
Generate <i>pagesetup</i>	
CreateExcelSheet::generateCOLS()	76
Generate <i>cols</i>	

CreateExcelSheet::generateDIMENSION()	76
<i>Generate dimension</i>	
CreateExcelSheet::generatePAGEMARGINS()	77
<i>Generate pagemargins</i>	
CreateExcelSheet::generateSHEETVIEWS()	79
<i>Generate sheetviews</i>	
CreateExcelSheet::generateTABLEPART()	79
<i>Generate tablepart</i>	
CreateExcelSheet::__toString()	81
CreateExcelTable	81
<i>Create excel table</i>	
constructor CreateExcelTable::__construct()	82
<i>Construct</i>	
CreateExcelSheet::__destruct()	81
<i>Destruct</i>	
CreateExcelSheet::getInstance()	81
CreateExcelSheet::generateTABLEPARTS()	80
<i>Generate tableparts</i>	
CreateExcelSheet::generateV()	80
<i>Generate v</i>	
CreateExcelSheet::generateWORKSHEET()	80
<i>Generate worksheet</i>	
CreateExcelSheet::generateCOL()	76
<i>Generate col</i>	
CreateExcelSheet::generateC()	75
<i>Generate c</i>	
CreateElement::__toString()	72
CreateExcelSharedStrings	72
<i>Generate excel shared strings</i>	
constructor CreateExcelSharedStrings::__construct()	72
<i>Construct</i>	
CreateElement::__destruct()	71
<i>Destruct</i>	
CreateElement::generateXFRM()	71
<i>Generate w:xfrm</i>	
CreateElement::generateWRAPSQUARE()	70
<i>Generate w:wrapsquare</i>	
CreateElement::generateWRAPTHROUGH()	71
<i>Generate w:wrapthrough</i>	
CreateElement::generateWRAPTOPANDBOTTOM()	71
<i>Generate w:wraptopandbottom</i>	
CreateExcelSharedStrings::createExcelSharedStrings()	72
<i>Create excel shared strings</i>	
CreateExcelSharedStrings::generateSI()	73
<i>Generate si</i>	
CreateExcelSheet	74
<i>Create excel sheet</i>	
constructor CreateExcelSheet::__construct()	75
<i>Construct</i>	
CreateExcelSheet::createExcelSheet()	75
<i>Create excel sheet</i>	
CreateExcelSharedStrings::__toString()	74
CreateExcelSharedStrings::__destruct()	74

<i>Destruct</i>	
CreateExcelSharedStrings::generateSST()	73
<i>Generate sst</i>	
CreateExcelSharedStrings::generateT()	73
<i>Generate t</i>	
CreateExcelSharedStrings::getInstance()	74
CreateExcelTable::createExcelTable()	82
<i>Create excel table</i>	
CreateExcelTable::generateTABLE()	82
<i>Generate table</i>	
CreateFooter::generatePTAB()	90
<i>Generate w:ptab</i>	
CreateFooter::generateR()	90
<i>Generate w:r</i>	
CreateFooter::getInstance()	90
CreateFooter::generateP()	90
<i>Generate w:p</i>	
CreateFooter::generateFTR()	89
<i>Generate ftr token</i>	
constructor CreateFooter:: __construct()	89
<i>Construct</i>	
CreateFooter::createFooter()	89
<i>Create footer</i>	
CreateFooter::generateFLDSIMPLE()	89
<i>Generate w:fldsimple</i>	
CreateFooter:: __destruct()	91
<i>Destruct</i>	
CreateFooter:: __toString()	91
CreateFootnote::createInitFootnote()	92
<i>Create init footnote</i>	
CreateFootnote::generateFOOTNOTE()	93
<i>Generate w:footnote</i>	
CreateFootnote::generateFOOTNOTEREF()	93
<i>Generate w:footnoteref</i>	
CreateFootnote::createFootnote()	92
<i>Create footnote</i>	
CreateFootnote::createDocumentFootnote()	92
<i>Create document footnote</i>	
CreateFootnote	91
<i>Create footnote</i>	
CreateFootnote::\$init	91
constructor CreateFootnote:: __construct()	92
<i>Construct</i>	
CreateFooter	88
<i>Create footer</i>	
CreateFontTable:: __toString()	88
CreateExcelTable:: __toString()	84
CreateFontTable	84
<i>Create font table</i>	
CreateFontTable::\$ xml	85
CreateExcelTable:: __destruct()	84
<i>Destruct</i>	
CreateExcelTable::getInstance()	84

CreateExcelTable::generateTABLECOLUMN()	82
<i>Generate tablecolumn</i>	
CreateExcelTable::generateTABLECOLUMNS()	83
<i>Generate tablecolumns</i>	
CreateExcelTable::generateTABLESTYLEINFO()	83
<i>Generate tablestyleinfo</i>	
constructor CreateFontTable:: __construct()	85
<i>Construct</i>	
CreateFontTable::createFont()	85
<i>Create font</i>	
CreateFontTable::generateSIG()	87
<i>Generate w:sig</i>	
CreateFontTable::getInstance()	88
CreateFontTable:: __destruct()	88
<i>Destruct</i>	
CreateFontTable::generatePITCH()	87
<i>Generate w:pitch</i>	
CreateFontTable::generatePANOSE1()	86
<i>Generate w:panose1</i>	
CreateFontTable::generateCHARSET()	85
<i>Generate w:charset</i>	
CreateFontTable::generateFAMILY()	86
<i>Generate w:family</i>	
CreateFontTable::generateFONT()	86
<i>Generate w:font</i>	
CreateDocx.inc	2
<i>Generate a DOCX file</i>	

T

TransformDoc::setstrFile()	211
<i>Setter. File</i>	
TransformDoc::getStrXHTML()	211
<i>Getter. XHTML</i>	
TransformDoc::getStrOutputFile()	211
<i>Getter. Output file</i>	
TransformDoc::setStrOutputFile()	212
TransformDoc::setStrXHTML()	212
<i>Setter. XHTML</i>	
TransformDoc:: __destruct()	213
<i>Destruct</i>	
TransformDoc::validatorXHTML()	212
<i>Validate HTML using tidy</i>	
TransformDoc::getstrFile()	211
<i>Getter. File</i>	
TransformDoc::getFileName()	211
<i>Return file name</i>	
TransformDoc::SCHEMA_OFFICEDOCUMENT	209
TransformDoc::SCHEMA_IMAGEDOCUMENT	209
TransformDoc	209
<i>Transform DOCX to PDF or XHTML</i>	
TransformDoc::absoluteZipPath()	210

<i>Return zip path</i>	
TransformDoc::cleanXHTML()	210
<i>Clean HTML</i>	
TransformDoc::generateXHTML()	210
<i>Convert DOCX to XHTML</i>	
TransformDoc::generatePDF()	210
<i>Convert DOCX to PDF, using dompdf. DOCX->XHTML->PDF</i>	
TransformDoc.inc	51
<i>Transform DOCX to PDF or XHTML</i>	